

**CALLA®**  
 Square Lay-in, Tegular  
 smooth texture



plus...  
 capabilities  
 to do more

armstrongceilings.com/capabilities  
 See more photos at:  
 armstrongceilings.com/photogallery

Calla® Square Tegular panels with Suprafine® 9/16" suspension system (Pgs. 400-401)

The smoothest finish mineral fiber ceiling available with Total Acoustics® performance – excellent noise reduction and sound blocking in one product.

**KEY SELECTION ATTRIBUTES**

- Get total noise control and design flexibility with Total Acoustics® ceiling panels: NRC + CAC = Total Acoustics® performance
- Calla® panels are part of the Sustain™ portfolio and meet the most stringent sustainability compliance standards today
- Available in 14 standard Colorations® colors with coordinating suspension systems and trim. Made-to-order Sherwin-Williams® colors available

- Excellent combination of acoustical performance; NRC (0.85), AC (170), and CAC (35) (White only)
- USDA-Certified Biobased Product – 59%
- Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Product can be recycled through the Armstrong Ceilings Recycling Program
- Compatible with the TechZone® Ceiling Systems (White only)
- 30-Year Limited System Warranty against visible sag, mold, and mildew

**TYPICAL APPLICATIONS**

- Offices – closed spaces for privacy and focus; open spaces for focus, collaboration, and teaming
- Healthcare – assists in addressing HIPAA, HCAHPS, and FGI acoustical requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail

**COLORATIONS® COLORS\*** Due to printing limitations, shade may vary from actual product.



\* Colorations colors are not included in the Sustain™ portfolio

**DETAILS** (Other Suspension Systems compatible. Refer to listing on page 222.)



1. Calla® Square Tegular
2. Calla Square Lay-in
3. Calla Square Tegular with Suprafine 9/16" suspension system

# CALLA®

## Square Lay-in, Tegular smooth texture




Declare™  
Living Building  
Challenge Compliant

SUSTAIN™  
High Performance  
Sustainable  
Ceiling Systems

76% RECYCLED CONTENT

Calculate LEED contribution at  
armstrongceilings.com/greengenie



### VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411	Item No.	Dimensions (Inches)
	armstrongceilings.com/catdwgs		

#### CALLA® Square Lay-in

15/16" Square Lay-in	1	<b>2820</b>	24 x 24 x 1"
	1	<b>2820BK</b>	24 x 24 x 1"
	1	<b>2821</b>	24 x 48 x 1"

#### CALLA Tegular

15/16" Square Tegular	8	<b>2822</b>	24 x 24 x 1"
	8	<b>2823</b>	24 x 48 x 1"
9/16" Square Tegular	43, 47, 26, 51, 55	<b>2824_♦♦</b>	24 x 24 x 1"
	43, 47, 26, 51, 55	<b>2825</b>	24 x 48 x 1"
43, 47, 26, 51, 55	<b>Other Size Panels</b>	W: 4" - 30" / L: 4" - 30" / W: 4" - 24" / L: 4" - 60" / 1" thick	N/A

### PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics		Total Acoustics <sup>1</sup>	Articulation Class	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Wash	Impact	Scratch	Soil	Recycled Content	Recycle Program	30-Yr Warranty
NRC	+ CAC	NRC + CAC	AC		(White Only)	Bio-Block	Humi-Guard+								
0.85	35	<b>BEST</b>	170	Class A	0.86	•	•	•	•	•	•	•	•	•	•
•	•		•	•	•	•	•	•	•	•	•	•	•	•	•
0.85	35	<b>BEST</b>	170	Class A	0.86	•	•	•	•	•	•	•	•	•	•
•	•		•	•	•	•	•	•	•	•	•	•	•	•	•
0.85	35	<b>BEST</b>	170	Class A	0.86	•	•	•	•	•	•	•	•	•	•
•	•		•	•	•	•	•	•	•	•	•	•	•	•	•
0.85	35	<b>BEST</b>	170	Class A	0.86	•	•	•	•	•	•	•	•	•	•
•	•		•	•	•	•	•	•	•	•	•	•	•	•	•
N/A	N/A	–	N/A	Class A	0.86	•	•	•	•	•	•	•	•	•	•
					•	•	•	•	•	•	•	•	•	•	•


\$\$\$



MINERAL FIBER

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.  
**GOOD** (NRC 0.60-0.65; CAC 35+) **BETTER** (NRC 0.70-0.75; CAC 35+) **BEST** (NRC 0.80+; CAC 35+)  
 ♦♦ Available in Colorations® standard colors. When specifying or ordering Calla Colorations panels, add the 2-letter suffix to the end of the item number (e.g., 2824LA – Lagoon)  
 Colorations colors are not included in the Sustain™ portfolio

### SUSPENSION SYSTEMS



### PHYSICAL DATA

**Material**  
Wet-formed mineral fiber with acoustically transparent membrane

**Surface Finish**  
Acoustically transparent membrane with factory-applied latex paint

**Fire Performance**  
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled).

**ASTM E1264 Classification**  
Type IV, Form 2, Pattern E  
Fire Class A

**Humidity/Sag Resistance**  
HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

**Mold/Mildew Protection**  
Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

**VOC Emissions**  
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

**Design Considerations**  
Combining materials with different run dates may result in shade variations. Order attic stock for any anticipated future needs.

**Acoustical Performance**  
CAC testing conducted using Prelude® XL® suspension system for 15/16" edge detail and Silhouette® suspension

system for 9/16" edge detail. NRC test conducted using white panels. Painted panels may experience a slight reduction in NRC due to the color painting process.

**High Recycled Content**  
Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

**Insulation Value**  
R Factor – 2.9 (BTU units)  
R Factor – 0.445 (Watts units)

**30-Year Performance Guarantee & Warranty**  
When installed with Armstrong® Suspension System. Details at armstrongceilings.com

**Weight; Square Feet/Carton**  
2820, 2822, 2824 – 1.0 lbs/SF; 40 SF/ctn  
2821, 2823, 2825 – 1.0 lbs/SF; 48 SF/ctn

TechLine™ / 1 877 276 7876  
armstrongceilings.com/commercial  
(search: calla)  
BPCS-4722-617

LEED® is a registered trademark of the U.S. Green Building Council  
 Sherwin-Williams® is a registered trademark of The Sherwin-Williams Company. Declare™ is a service mark of The International Living Future Institute. UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates  
 © 2017 AWI Licensing LLC Printed in the United States of America



CEILING & WALL SOLUTIONS