



CASE STUDIES

WHEN IT COMES TO COMMERCIAL DRYWALL, ONE SIZE DOES NOT FIT ALL

Introducing SHEETROCK® UltraLight Panels FIRECODE® 30



THE NAME
PROS TRUST®

40% of all 5/8" type X panels are currently installed in non-fire-rated applications. CGC now offers you a choice with SHEETROCK® UltraLight Panels FIRECODE® 30—an optimally designed lightweight alternative to standard 5/8" type X panels.*

Non-rated wall opportunity — Project examples:



California Pacific Medical Center



Cavellero Mid High School



USG Headquarters

Total Linear Feet of Walls133,245
Percentage of Non-Rated Walls48%
 Fire-Rated Wall Breakdown:
 1-hour rated walls35%
 2-hour stud walls4%
 2-hour shaft walls13%
 3-hour rated walls0.5%
 Source: SmithGroup Architects—BIM technology

Percentage of Non-Rated Walls88%
 Source: NAC Architects—Seattle, WA

Total Sq. Ft. of Gypsum Wallboard500,000
Percentage of Non-Rated Walls80%
 Source: The Environments Group— Now part of Perkins + Will

Another first from CGC, The Leader in Lightweight Innovation™.

*A lightweight alternative optimally designed for use where standard 5/8" type X panels are not required to meet one-hour fire rating or specific sound performance applications.
 MK_P_CSDOC_FC30_E 2-12 © 2012 CGC Inc. The CGC logo is a trademark of CGC Inc. CGC Inc. is a licensed user of the following trademarks: THE LEADER IN LIGHTWEIGHT INNOVATION, SHEETROCK, FIRECODE and THE NAME PROS TRUST.

TheWeightHasBeenLifted.com

