

DUNE™


Square Lay-in & Tegular
fine texture



1772, 1773, 1774, 1775, 1776



Dune™ Square Lay-in panels with Prelude® XL 15/16" suspension system
(Pgs. 391-392)



Dune Tegular panels with Interlude® XL HRC 9/16" suspension system
(Pgs. 385-386)

This durable, fine-textured panel offers a non-directional visual.

KEY SELECTION ATTRIBUTES

- Upgrade look at a modest price
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 1773HRC, 1774HRC, 1775HRC, 1776HRC, 1777HRC (check armstrongceilings.com/greengenie)
- USDA-Certified Biobased Product – 100%
- Durable – Scratch-resistant
- Non-directional visual reduces scrap and installation time
- 30-Year Limited System Warranty against visible sag (excludes items 1796 and 1798), mold and mildew

TYPICAL APPLICATIONS

- Offices
- Corridors
- Retail
- Hospitality

COLOR



White
(WH)

DETAILS (Other Suspension Systems compatible. Refer to listing on page 250)























1. Dune™ Tegular
2. Dune™ Square Lay-in with Prelude 15/16" suspension system
3. Dune™ Tegular with Suprafine® 9/16" suspension system
4. Dune™ Tegular with Silhouette® XL 9/16" suspension system with 1/4" reveal
5. Dune™ Tegular with Interlude® XL HRC 9/16" suspension system

DUNE™


Square Lay-in & Tegal
fine texture

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411 armstrongceilings.com/catdwgs	Item No.	Dimensions (Inches)	
DUNE™ Square Lay-in				
	1	1772	24 x 24 x 5/8"	
	1	1850	24 x 24 x 5/8"	
	1	 1773 1773HRC	24 x 48 x 5/8"	
	1	1851	24 x 48 x 5/8"	
	1	1796	20 x 60 x 3/4"	
	1	1798	30 x 30 x 3/4"	
1		Other Size Panels	W: 12" – 30" / L: 18" – 72" 5/8" or 3/4" Thick	
DUNE Tegal				
	12	 1774 1774HRC	24 x 24 x 5/8"	
	12	1853	24 x 24 x 5/8"	
	12	 1776 1776HRC	24 x 48 x 5/8"	
	12	Other Size Panels	W: 12" – 30" / L: 18" – 72" 5/8" Thick	
	29, 44, 48, 52, 56	 1775 1775HRC	24 x 24 x 5/8"	
	29, 44, 48, 52, 56	1852	24 x 24 x 5/8"	
	29, 44, 48, 52, 56	 1777 1777HRC	24 x 48 x 5/8"	
	29, 44, 48, 52, 56	Other Size Panels	W: 12" – 30" / L: 18" – 72" 5/8" Thick	

1 Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled). Fire Guard™: A fire-resistive ceiling when used in applicable UL assemblies (Class A).

ASTM E1264 Classification

Type III, Form 2, Pattern C E
Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications. Excludes items 1796, 1798, and large other size panels.

Mold/Mildew Protection

Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

Acoustical Performance

CAC testing conducted using Silhouette® suspension system.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Primary (Embodied) Energy

See all LCA information on our EPDs.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines. HRC items contain 15% or greater post-consumer recycled ceilings.

Insulation Value

R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrongceilings.com (Excludes items 1796, 1798, and large other size panels)

Weight; Square Feet/Carton

1772 – 0.94 lbs/SF; 64 SF/ctn
1773 – 0.88 lbs/SF; 64 SF/ctn
1796 – 1.33 lbs/SF; 67 SF/ctn
1798 – 1.14 lbs/SF; 50 SF/ctn
1850 – 1.19 lbs/SF; 48 SF/ctn
1851 – 1.22 lbs/SF; 64 SF/ctn
1774, 1775 – 0.75 lbs/SF; 64 SF/ctn
1776, 1777 – 0.75 lbs/SF; 64 SF/ctn
1852, 1853 – 1.20 lbs/SF; 48 SF/ctn

Minimum Order Quantity

1 carton, excludes other size panels

Metric Items Available

1772M, 1850M, 1773M, 1851M, 1796M, 1798M, 1775M, 1777M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.

TechLine / 1 877 276-7876
armstrongceilings.com/commercial
(search: dune)
BPCS-4351-517

LEED® is a registered trademark of the U.S. Green Building Council
UL is a registered trademark of UL LLC. All other trademarks used herein are the property of AWI Licensing LLC and/or its affiliates
© 2016-2017 AWI Licensing LLC Printed in the United States of America

Armstrong®
CEILING & WALL SOLUTIONS

250



UP TO **56%** RECYCLED CONTENT

Calculate LEED contribution at armstrongceilings.com/greengenie

LEED®

energy management
construction waste mgmt
regional materials
design for flexibility
EPD
recyclable/extended producer resp.
biobased materials
recycled content
sourcing of raw materials
material ingredient reporting
low emitting materials
lighting quality
acoustics

LOCATION DEPENDENT

PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$

UL Classified Acoustics	NRC	+	CAC	=	Total Acoustics ¹	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Scratch	Recycled Content	Recycle Program	30-Yr Warranty
								Bio-Block	Humi-Guard+		Durability			
0.50	30	–	Class A	0.83	•	•	•	•	•	•	Std	•	•	•
0.50	35	–	Fire Guard™	0.83	•	•	•	•	•	•	Std	•	•	•
0.50	30	–	Class A	0.83	•	•	•	•	•	•	Std	•	•	•
0.50	35	–	Fire Guard	0.83	•	•	•	•	•	•	Std	•	•	•
0.50	35	–	Class A	0.83	•	•	Std	•	•	•	•	•	•	1-Yr
0.50	35	–	Class A	0.83	•	•	Std	•	•	•	•	•	•	1-Yr
N/A	N/A	–	Class A	0.83	•	•	Std	•	•	•	Std	•	•	1-Yr
0.50	35	–	Class A	0.83	•	•	•	•	•	•	Std	•	•	•
0.50	35	–	Fire Guard	0.83	•	•	•	•	•	•	Std	•	•	•
0.50	35	–	Class A	0.83	•	•	•	•	•	•	Std	•	•	•
N/A	N/A	–	Class A	0.83	•	•	Std	•	•	•	Std	•	•	1-Yr
0.50	35	–	Class A	0.83	•	•	•	•	•	•	Std	•	•	•
0.50	35	–	Fire Guard	0.83	•	•	•	•	•	•	Std	•	•	•
0.50	35	–	Class A	0.83	•	•	•	•	•	•	Std	•	•	•
N/A	N/A	–	Class A	0.83	•	•	Std	•	•	•	Std	•	•	1-Yr



MINERAL FIBER