

# DUNE™ Second Look®

Scored Regular  
fine texture



Dune™ Second Look® I panels with Prelude® 15/16" suspension system (Pgs. 391-392)

This fine-textured visual offers geometric scored visuals.

## KEY SELECTION ATTRIBUTES

- Upgrade look at a modest price
- USDA Certified Biobased Content – 100%
- Durable – Scratch-resistant
- 30-Year Limited System Warranty against visible sag, mold, and mildew

## TYPICAL APPLICATIONS

- Specialty shops/stores
- Corridors
- Offices

## FACE VIEW



Second Look I panel –  
Scoring creates nominal 12" x 12" squares





Second Look II panel –  
Scoring creates nominal 24" x 24" squares

## COLOR



White  
(WH)

## DETAILS (Other Suspension Systems compatible. Refer to listing on page 252.)



1. Dune® Second Look®
2. Dune Second Look with Suprafine®  
9/16" suspension system

# DUNE™ Second Look®

Scored Tegular  
fine texture

UP TO 41% RECYCLED CONTENT




Calculate LEED contribution at [armstrongceilings.com/greengenie](http://armstrongceilings.com/greengenie)

LEED®

energy management  
construction waste mgmt  
regional materials  
design for flexibility  
EPD  
recyclable/extended producer resp.  
biobased materials  
recycled content  
sourcing of raw materials  
material ingredient reporting  
low emitting materials  
lighting quality  
acoustics

LOCATION DEPENDENT

## VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 407-411 <a href="http://armstrongceilings.com/catdwgs">armstrongceilings.com/catdwgs</a>	Item No.	Dimensions (Inches)
<b>DUNE™ Second Look® I</b>			
15/16" Angled Tegular	11	2711	24 x 48 x 3/4" 
<b>DUNE Second Look II</b>			
15/16" Angled Tegular	11	2712	24 x 48 x 3/4" 
9/16" Angled Tegular	27	2722	24 x 48 x 3/4" 


## PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics		=	Total Acoustics <sup>1</sup>	Fire Performance	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Scratch	Recycled Content	Recycle Program	30-Yr Warranty
NRC	+ CAC											
0.50	35		—	Class A	0.83	•	•	•	•	Std	•	•
0.50	35		—	Class A	0.83	•	•	•	•	Std	•	•
0.50	35		—	Class A	0.83	•	•	•	•	Std	•	•

<sup>1</sup> Total Acoustics® ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

## SUSPENSION SYSTEMS



## PHYSICAL DATA

### Material

Wet-formed mineral fiber

### Surface Finish

Factory-applied latex paint

### Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled).

### ASTM E1264 Classification

Type III, Form 2, Pattern C E K  
Fire Class A

### Humidity/Sag Resistance

HumiGuard® Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

### Mold/Mildew Protection

Ceiling panels with BioBlock® performance resist the growth of mold and mildew.

### VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

### Insulation Value

R Factor – 1.6 (BTU units)  
R Factor – 0.28 (Watts units)

### Design Consideration

Do not mix Dune™ Second Look® with standard Dune panels in the same room.

### 30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at [armstrongceilings.com](http://armstrongceilings.com)

### Weight; Square Feet/Carton

1.00 lbs/SF; 80 SF/ctn

### Minimum Order Quantity

1 carton

### Metric Items Available

2711M, 2722M, 2712M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.