

Submittal Sheet

Submittal Sheet #03090414-H

Hex Head Drivall® Screws (246)

Product:	Item#	Description	Unit Pack
	08050H3	8 x 1/2-in, Hex Head, Drivall®, Clear Zinc, Bulk	10,000
	12150H3RG	12 x 1-1/2-in, Hex Head, Drivall®, GrabberGard, Bulk	3,500
	1224200H5SL	12-24 x 2-in Hex Head, Slot Shank, #5 Drill Point, Clear Zinc, Bulk	1000
	08058H3	8 x 5/8-in, Hex Head, Drivall®, Clear Zinc, Bulk	10,000
	1224300H4RG	12-24 X 3-in, Hex Head, Drivall®, T-4 Point, GrabberGard®, Bulk	1,000
	1224200H4RG	12-24 x 2-in, Hex Head, Drivall®, T-4 Point, GrabberGard®, Bulk	2,000
	1224200H5RG	12-24 x 2-in, Hex Head, Drivall®, T-5 Point, GrabberGard®, Bulk	2,000
	1224150H5RG	12-24 x 1-1/2-in, Hex Head, Drivall®, T-5 Point, GrabberGard®, Bulk	2,000
	1224150H4RG	12-24 x 1-1/2-in, Hex Head, Drivall®, T-4 Point, GrabberGard®, Bulk	2,500
	1224125H5RG	12-24 x 1-1/4-in, Hex Head, Drivall®, T-5 Point, GrabberGard®, Bulk	3,500
	122478H4RG	12-24 x 7/8-in, Hex Head, Drivall®, T-4 Point, GrabberGard®, Bulk	5,000
	14300H3WRG	14 X 3-in, Hex Washer Head, Neoprene Washer, Drivall®, 3-Point, GrabberGard®, Bulk	1,000
	10100H	10 x 1-in, Hex Head Drivall®, Clear Zinc, Bulk	5,000
	10100H3	10 x 1-in, Hex Head, Drill Point, Clear Zinc, Bulk	5,000
	10100HA	10 x 1-in, Hex Washer Head, Drivall®, Clear Zinc, Bulk	5,000
	10150H3RG	10 x 1 1/2-in, Hex Head, Drivall®, GrabberGard®, Bulk	3,500
	10150H	10 x 1-1/2-in, Hex Head Drivall®, Clear Zinc, Bulk	3,500
	10150H3	10 x 1-1/2-in, Hex Head, Drivall®, Clear Zinc, Bulk	3,500
	10125H	10 x 1-1/4-in, Hex Head Drivall®, Clear Zinc, Bulk	5,000
	10125H3	10 x 1-1/4-in, Hex Head, Drivall®, Clear Zinc, Bulk	5,000
	10050H	10 x 1/2-in, Hex Head Drivall®, Clear Zinc, Bulk	7,500
	10050H3	10 x 1/2-in, Hex Head, Drivall®, Clear Zinc, Bulk	7,500
	10200H3	10 x 2-in, Hex Head, Drivall®, Clear Zinc, Bulk	3,000
	10300H3	10 x 3-in, Hex Head Drivall®, Clear Zinc, Bulk	1,500
	10075H	10 x 3/4-in, Hex Head Drivall®, Clear Zinc, Bulk	5,000
	10075H3	10 x 3/4-in, Hex Head, Drivall®, Clear Zinc, Bulk	5,000
	10058H	10 x 5/8-in, Hex Head Drivall®, Clear Zinc, Bulk	7,500
	10058H3	10 x 5/8-in, Hex Head, Drivall®, Clear Zinc, Bulk	7,500
	12100H	12 x 1-in, Hex Head Drivall®, Clear Zinc, Bulk	3,500
	12100H3	12 x 1-in, Hex Head, Drivall®, Clear Zinc, Bulk	3,500
	12150H3	12 x 1-1/2-in, Hex Head, Drivall®, Clear Zinc, Bulk	2,500
	12125H	12 x 1-1/4-in, Hex Head Drivall®, Clear Zinc, Bulk	3,500
	12125H3SS	12 x 1-1/4-in, Hex Head, Drivall®, 410 Stainless Steel, T-3 Point, Bulk	2,500
	12125H3	12 x 1-1/4-in, Hex Head, Drivall®, Clear Zinc, Bulk	3,500
	12200H3	12 x 2-in, Hex Head, Drivall®, Clear Zinc, Bulk	3,500
	12250H3	12 x 2-1/2-in, Hex Head, Drivall®, Clear Zinc, Bulk	1,500
	12300H3	12 x 3-in, Hex Head, Drivall®, Clear Zinc, Bulk	1,000
	12350H3	12 x 3-1/2-in, Hex Head, Drivall®, Clear Zinc, Bulk	1,000
	12075H	12 x 3/4-in, Hex Head Drivall®, Clear Zinc, Bulk	5,000
	12075H3	12 x 3/4-in, Hex Head, Drivall®, Clear Zinc, Bulk	5,000
	1224125H4	12 x 1-1/4-in, Hex Head, Drivall®, 24TPI, Clear Zinc, Bulk	3,500

122478H4	12 x 7/8-in, Hex Head, Drivall®, 24TPI, Clear Zinc, Bulk	3,500
14100H3	14 x 1-in, Hex Head, Drivall®, Clear Zinc, Bulk	3,500
14100H	Hex Head Driller 14 x 1", Bulk	3.5 M
14150H3	14 x 1-1/2-in, Hex Head, Drivall®, Clear Zinc, Bulk	2,000
14125H	14 x 1-1/4-in, Hex Head Drivall®, Clear Zinc, Bulk	2,000
14125H3	14 x 1-1/4-in, Hex Head, Drivall®, Clear Zinc, Bulk	2,000
14200H	14 x 2-in, Hex Head Drivall®, Clear Zinc, Bulk	1,500
14200H3	14 x 2-in, Hex Head, Drivall®, Clear Zinc, Bulk	1,500
14250H	14 x 2-1/2-in, Hex Head Drivall®, Clear Zinc, Bulk	1,000
14250H3	14 x 2-1/2-in, Hex Head, Drivall®, Clear Zinc, Bulk	1,000
14300H3	14 x 3-in, Hex Head, Drivall®, Clear Zinc, Bulk	1,000
14075H	14 x 3/4-in, Hex Head Drivall®, Clear Zinc, Bulk	5,000
14075H3	14 x 3/4-in, Hex Head, Drivall®, Clear Zinc, Bulk	5,000
14400H4	14 x 4-in, Hex Head, Drivall®, Clear Zinc, Bulk	500
06050H	6 x 1/2-in, Hex Head Drivall®, Clear Zinc, Bulk	15,000
08100H	8 x 1-in, Hex Head Drivall®, Clear Zinc, Bulk	7,500
08100HA	8 x 1-in, Hex Head Drivall®, Clear Zinc, Bulk	7,500
08100H3	8 x 1-in, Hex Head, Drivall®, Clear Zinc, Bulk	7,500
08125H3	8 x 1-1/4-in, Hex Head, Drill Point, Clear Zinc, Bulk	5,000
08050H	8 x 1/2-in, Hex Head Drivall®, Clear Zinc, Bulk	10,000
08200H3	8 x 2-in, Hex Head, Drivall®, Clear Zinc, Bulk	3,000
08075H	8 x 3/4-in, Hex Head Drivall®, Clear Zinc, Bulk	10,000
08075H3	8 x 3/4-in, Hex Head, Drivall®, Clear Zinc, Bulk	10,000
08058H	8 x 5/8-in, Hex Head Drivall®, Clear Zinc, Bulk	10,000
12075HA	12 x 3/4-in, Hex Head, Drivall®, Clear Zinc, Bulk	5,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Drivall	Heavy Gauge Steel	Hex Washer Head	0.164	0.335	#8-18	1	Drill #3	1	20 ga.	12 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.164	0.335	#8-18	1.25	Drill #3	1.25	20 ga.	12 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.164	0.335	#8-18	0.5	Drill #3	0.5	20 ga.	12 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.164	0.335	#8-18	2	Drill #3	2	20 ga.	12 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.164	0.335	#8-18	0.75	Drill #3	0.75	20 ga.	12 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.164	0.335	#8-18	0.625	Drill #3	0.625	20 ga.	12 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.19	0.399	#10-16	1	Drill #3	1	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.19	0.399	#10-16	1.5	Drill #3	1.5	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.19	0.399	#10-16	1.25	Drill #3	1.25	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.19	0.399	#10-16	0.5	Drill #3	0.5	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.19	0.399	#10-16	2	Drill #3	2	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.19	0.399	#10-16	3	Drill #3	3	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.19	0.399	#10-16	0.75	Drill #3	0.75	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.19	0.399	#10-16	0.625	Drill #3	0.625	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-14	1	Drill #3	1	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-14	1.5	Drill #3	1.5	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-14	1.25	Drill #3	1.25	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-14	2.5	Drill #3	2.5	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-14	3	Drill #3	3	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-14	3.5	Drill #3	3.5	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-14	0.75	Drill #3	0.75	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.25	0.5	#14-14	1	Drill #3	1	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.25	0.5	#14-14	1.5	Drill #3	1.5	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.25	0.5	#14-14	1.25	Drill #3	1.25	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.25	0.5	#14-14	2	Drill #3	2	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.25	0.5	#14-14	2.5	Drill #3	2.5	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.25	0.5	#14-14	3	Drill #3	3	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.25	0.5	#14-14	0.75	Drill #3	0.75	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.25	0.5	#14-14	4	Drill #4	4	20 ga.	8 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-24	1.5	Drill #4	1	18 ga.	10 ga.	RG
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-24	1.25	Drill #4	0.75	18 ga.	10 ga.	Z
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-24	2	Drill #4	1.5	18 ga.	10 ga.	RG
Drivall	Heavy Gauge Steel	Hex Washer Head	0.216	0.415	#12-24	0.875	Drill #4	0.375	18 ga.	10 ga.	Z

NOTE: Grabber screws with the item numbers ending in "A" are manufactured in the United States of America. Grabber American Made Screws are SPECIAL ORDER INVENTORY. CONTACT GRABBER FOR CURRENT PRICE AND AVAILABILITY.

Application: Attaches fixtures, backup plates, door frames and lathers channel to structural studs, metalchecks, etc. 20-8 ga.

Description: Hex head framing screw used in heavy gauge metal to metal applications where high torque is required. Self tapping drill point is designed for penetration into heavy gauge metal. Hex head provides maximum driving torque with a flat bearing surface. Also available with #3 point.

Directions: Use a standard screwgun with a depth sensitive nose piece. Suggested screwgun specification for optimal performance – 4 amps minimum and RPM range of 0 to 2,500. The Hex head is fully seated when the head is flush with the work surface. Overdriving may result in failure of the fastener or stripout of the work surface. The fastener must penetrate beyond the metal a minimum of three thread pitches.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASTM C1513, as referenced in ICC ESR report ESR-1271, are approved for use in structures governed by the International Building Code 2006, 2009, 2012, International Residential Building Code 2006, 2009, and 2012.

SUBMITTAL APPROVALS:

.....
JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Hex Head Drivall® Screws (246)



PRODUCT SPECIFICATIONS

Fastener Classification	Heavy Gauge Metal, Heavy Gauge Metal (18 or thicker)
Fastener Head	Hex
Fastener Drive	Hex
Fastener Gauge	#6, #8, #10, #12, #14, #12-24
Fastener Point	Drill, Drill, S-12, #2.5 Drill, #3 Drill, #4 Drill, #5 Drill
Fastener Package Type	Packaged Screws
Fastener Package Weight	Mini Pack, 1lb Box, 5 Pound, 5lb Box, Bulk Box
Fastener TPI	14, 16, 18, 20, 24
Fastener Coating	302 Stainless Steel, Clear Zinc, GrabberGard

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.