

At CGC, we know that settling for "good enough" is never an option. You need reliable, high-quality products that you can depend on every time.

For more than 100 years, CGC has been the leading manufacturer of the highest-performing building materials within the industry. So you can trust that when you choose our products, you're always getting the best possible quality.

We offer finishing products specifically designed to meet your needs, and a full portfolio that provides unique and adaptable solutions for a variety of environments.

Beyond outstanding products, we also offer expertise, technical support and nationwide availability. All driven by a dedication to finding solutions for you. Plus, we have the technology and manufacturing capabilities to ensure our products exceed industry standards before ever being introduced to the market.

We do all of this because we believe that our reputation is built on yours. When you succeed, we succeed. Your exceptional skill—combined with our solutions—lead to better experiences and quality finishes.

TABLE OF CONTENTS

FINISHING SOLUTIONS

Drywall Compounds	4-6
Joint Tapes	7
Bead and Trim	8-10
Strait-Flex®	
SURFACING SOLUTIONS	
Interior Texture Finishes	13
Plaster Finishes	13-15
Plaster Accessories	
PREPARATION SOLUTIONS	
Primers	16
INTERIOR PATCH & REPAIR SOLUTIONS	
Repair Products	17-18
QUICK REFERENCE GUIDES	19
CGC COMMODITY CODES	20-22



MONTREAL, QC

FINISHING SOLUTIONS

Offering the industry's broadest selection of finishing solutions, our high-quality drywall compounds, joint tapes, beads and trims deliver superior performance for every job, every time. Whether you're taping, applying a finish coat or patching a crack, there is a CGC finishing product to meet your needs.

Drywall Compounds

READY-MIXED DRYWALL COMPOUNDS CGC ready-mixed drywall compounds are drying-type products that are vastly superior to ordinary ready-mixed compounds and are preferred for consistently high-quality work. These formulations are specially premixed to a creamy, smooth consistency essentially free of crater-causing air bubbles. They offer excellent slip and bond and easy workability. Available for hand or machine-tool applications.

CGC Sheetrock® Brand All Purpose Drywall Compound



- Versatile-for all drywall joint finishing
- Recommended for skim coating and for laminating and repairing cracks in interior plaster and masonry not subject to moisture
- Great bond hard-finish surface
- Available in: 16 L carton, 12 L pail, 4.5 L pail, 2 L pail

For embedding CGC Sheetrock® Brand Paper Joint Tape and applying drywall filling and finishing coats. Also for covering fasteners, USG Sheetrock® Brand Paper-Faced Metal Corner Bead and Trim, skim coating drywall surfaces and hand-applying simple textures. For repairing cracks on drywall and plaster.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand All Purpose Lite Drywall Compound



- Smoother working and sands more easily than most other conventionalweight compounds
- Versatile—for all drywall joint finishing steps
- Less shrinkage-minimizes coats over corner bead
- · Regional availability with beige tint
- · Available in: 17 L carton

Less weight, less shrinkage (minimizes coats over corner bead) and easier to apply and sand than conventional weight drywall compounds. For embedding CGC Sheetrock® Brand Paper Joint Tape, applying drywall filling and finishing coats, covering fasteners and USG Sheetrock® Brand Paper-Faced Metal Corner Bead and Trim For hand-applying simple textures.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand Machine Mud® Drywall Compound



- · Ideal for use in mechanical finishing tools
- Versatile—for all drywall joint finishing steps
- · Easy to apply and sand, less shrinkage
- Available in: 17 L carton

Ideal in mechanical finishing tools, also for hand application. Less weight, less shrinkage (minimizes coats over corner bead), easier to apply and sand than conventional weight drywall compounds. For embedding CGC Sheetrock® Brand Paper Joint Tape, applying drywall filling and finishing coats, covering fasteners and USG Sheetrock® Brand Paper-Faced Metal Corner Bead and Trim. For hand-applying simple textures.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand X-Tra Lite™ Drywall Compound



- · For fill and finish coats in drywall ioint finishing
- · Less weight, easier to apply and sand
- · Good crack resistance and less shrinkage
- · Regional availability
- · Available in: 17 L carton

For the filling coat (second coat) and finishing coat (third coat) over embedded paper joint tape, corner bead, trim and fasteners. For all coats when covering USG Sheetrock® Brand Paper-Faced Metal Corner Bead and Trim. Do not use to embed joint tape, to apply the first coat over metal corner bead, trim and fasteners, to skim coat or to texture.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

READY-MIXED DRYWALL COMPOUNDS (CONT.)

CGC Sheetrock® Brand Lite-Weight Taping Drywall Compound



- · For embedding drywall paper joint tape
- · Less weight, easier to apply
- Superior bond and minimal shrinkage
- Regional availability
- · Available in: 17 L carton

Ideal for use in mechanical taping tools. Less weight, easier to apply than conventional drywall compound. For embedding CGC Sheetrock* Brand Paper Joint Tape. For applying USG Sheetrock* Brand Paper-Faced Metal Corner Bead and Trim on drywall and the first coat over bare metal corner bead, trim and fasteners. For skim coating drywall surfaces, hand-applying simple textures and patching cracks. Do not use for filling and finishing coats over joints.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand Total™ Drywall Compound



- Superior working qualities and good open time
- Versatile—for all drywall joint finishing steps
- Up to 35% less weight, easier to apply and sand
- · Superior bond and minimal shrinkage
- Regional availability
- Available in: 17 L carton

Up to 35% less weight, easier to apply and sand than conventional weight drywall compounds and provides excellent adhesion. For embedding CGC Sheetrock* Brand Paper Joint Tape, applying drywall filling and finishing coats, covering fasteners and USG Sheetrock* Brand Paper-Faced Metal Corner Bead and Trim. Also for skim coating drywall surfaces and hand-applying simple textures.

CGC Sheetrock® Brand Dust Control® Drywall Compound



- Unique formula binds up fine residue during sanding to form heavier particles that tend to fall to the floor instead of clouding the air
- Ideal for remodeling, less sanding mess
- Versatile—for all drywall finishing steps
- Less weight, easier to apply
- Available in: 17 L carton, 12 L pail,
 4.5 L pail, 2 L pail, 162 mL tube, Patch and Repair Kit

Reduces airborne sanding dust for faster clean-up—ideal for remodeling projects. Less weight, less shrinkage (minimizes coats over corner bead) and easier to apply and sand than conventional weight drywall compounds. For embedding CGC Sheetrock® Brand Paper Joint Tape, applying drywall filling and finishing coats. Also for covering fasteners, USG Sheetrock® Brand Paper-Faced Metal Corner Bead and Trim, and for hand-applying simple textures.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand UltraLight Drywall Compound



- Versatile—for all drywall joint finishing steps
- Up to 30% less weight, easier to apply
- Excellent taping and finishing performance
- Available in: 11.5 L pail

Easier to apply and handle than conventional weight drywall compounds. For embedding CGC Sheetrock* Brand Paper Joint Tape, applying drywall filling and finishing coats, and covering fasteners, USG Sheetrock* Brand Paper-Faced Metal Corner Bead and Trim, and skim coating drywall surfaces. Provides an easier to sand surface.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

SETTING-TYPE **DRYWALL COMPOUNDS**

CGC setting-type drywall compounds provide faster finishing of drywall interiors, even under slow drying conditions. Rapid chemical hardening and low shrinkage permit same-day finishing and usually next-day decoration. These products feature exceptional bond, virtually unaffected by humidity extremes. They are ideal for laminating double-layer systems, particularly fire-rated assemblies, and for adhering gypsum panels to above-grade concrete surfaces. May also be used for surface texturing and for filling, smoothing and finishing interior above-grade concrete. Note that setting-type drywall compounds should not be used for skim coating due to dryout concerns.

CGC Sheetrock® Brand Setting-Type Drywall Compound



- Available in 5-, 20-, 45- and 90-minute set times
- For one-day patching and joint finishing and next-day decoration
- Easy to sand
- Provides low shrinkage and a superior
- Ideal for laminating drywall and patching plaster surfaces
- Available in: 11 kg bag

Provides strong bond. For embedding drywall joint tape and applying drywall joint filling and finishing coats. For covering fasteners, USG Sheetrock® Brand Paper-Faced Metal Corner Bead and Trim, and filling and levelling interior above-grade concrete. For laminating drywall and patching drywall and plaster surfaces. Do not use as a skim coat.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand Durabond® Setting-Type Drywall Compound





- · Available in 45- and 90-minute set times
- · Exceptional bond with low shrinkage
- Same-day finishing and next-day decorating possible
- Excellent check-crack resistance in heavy fills
- Unique resistance to humidity
- · Available in: 15 kg bag

Provides strong bond. For embedding drywall joint tape, covering fasteners and USG Sheetrock® Brand Paper-Faced Metal Corner Bead and Trim. For filling and levelling interior above-grade concrete, laminating drywall and patching drywall and plaster surfaces. Do not use as a skim coat.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CONCRETE **LEVELLING** COMPOUND

CGC Sheetrock® Brand Cover Coat™ Levelling Compound



- · Conceals minor surface defects and irregularities
- Easy to apply with trowel or spray
- Provides high-strength bond
- Available in: 15 kg bag

An aggregated coating for filling and smoothing above-grade interior concrete ceilings and columns. Provides excellent slip for trowel application; allows fast and easy spray application. Levels irregularities and conceals minor surface defects. Provides excellent crack resistance. Dries to a white finish that may be overpainted.

Joint Tapes

PAPER JOINT TAPES

From the originator of modern joint finishing, CGC reinforcing tapes add strength and crack resistance for smooth concealment at flat joints and inside corners. CGC joint tapes are high-quality and easily applied, and are available for specialized uses.

To prevent cracking and ensure good joint performance, paper tape is always recommended. While the high-strength of setting-type compounds produces a strong joint with either paper or fiberglass mesh tape, even with setting-type compounds, paper joint tape performs best.

CGC Sheetrock® Brand Paper Joint Tape



- Superior center creasing for trouble-free corner finishing
- High strength to resist tearing, stretching or wrinkling
- Processed for superior bond
- Wafer thin for easy joint treatment
- Available in: 75' roll. 250' roll. 500' roll: 2-1/16" wide

High-performing paper tape that has strong, cross-directional fibers with high tensile strength for use with CGC drywall compounds to reinforce joints and corners in gypsum drywall interiors.

FIBERGLASS JOINT TAPES

While fiberglass mesh tape is stronger than paper tape in expansion under ultimate tensile load, it does not reinforce the drywall compound in compression, bending or shear, and will allow visible cracking of the drywall compound to occur at lower loads as the glass mesh stretches. The only time CGC recommends mesh tape is when you're using our fiberglass drywall tapes with CGC setting-type drywall compounds.

CGC Sheetrock® Brand Fiberglass Joint Tape



- · Self-adhesive tape-no bedding coat needed
- · Smooth joints in only two coats
- Use with setting-type drywall compounds for one-day joint finishing
- Available in: 65' roll, 300' roll, 500' roll; 2" wide

High number of strands-to-inch count makes it ideal for joints, cracks and small holes in drywall, plaster and ceilings.

CGC Sheetrock® Brand Mould-Resistant Fiberglass Joint Tape



- Moisture- and mould-resistant
- Self-adhesive tape—no bedding coat needed
- Smooth joints in only two coats
- Use with setting-type drywall compounds for one-day joint finishing
- Available in: 300' roll; 2" wide

Designed to provide increased moisture and mould protection. Self adhesion makes joint finishing simpler and quicker.

USG Imperial® Brand Tape: Type P



- For veneer plaster systems
- Type P for pressure-sensitive attachment
- Open weave of tape provides excellent keying of plaster during embedding
- · Produces highly crack-resistant veneer plaster assemblies
- Available in: 300' roll; 2-1/2" wide

Strong, glass-fiber tape for joint reinforcement in USG veneer plaster systems on wood framing.

Bead and Trim

PAPER-FACED METAL CORNER BEAD AND TRIM For the most cost-effective, problem-free, beautiful corners, choose USG Sheetrock® Brand Paper-Faced Metal Corner Bead and Trim. Fast, easy installation means reduced labour costs, while superior product performance eliminates costly job callbacks, saving money and ensuring customer satisfaction. Nailing is not required, so installation and corner alignment are easier, and there are no nails to pop when wood framing shrinks. Paper-faced metal technology provides excellent bond adhesion qualities for drywall compounds, textures and paints. The unique green "nose coating" on the paper tape covering resists scuffing and fuzzing from knives and sanding. The paper tape covering ensures excellent adhesion of drywall compounds, textures and paints for a strong, smooth finish.

USG Sheetrock® Brand Paper-Faced Metal Corner Bead and Trim provide superior resistance to edge cracking and chipping for a look that stays beautiful despite the stresses of normal building movement and everyday wear and tear. In fact, CGC warrants that its beads and trims will not edge crack for the lifetime of the structure using recommended application techniques.


90° AND OFFSET OUTSIDE CORNER BEAD USG Sheetrock* Brand Paper-Faced Metal Corner Bead Outside Corner (B1W, B1XW, B1 Super Wide) Use for 90° outside corners. Suitable for use on any thickness of wallboard. Standard lengths: 8′, 9′, 10′. Meets ASTM C1047.



Dimensions

Style	A	В	С	D
B1W	3/4"	13/16"	9/16"	3/4"
B1XW EL	5/8"	13/16"	13/16"	5/8"
B1 Super Wide	11/16"	1-1/16"	1-1/16"	11/16"

Note: XW = Extra Wide; EL = Even Leg



USG Sheetrock* Brand Paper-Faced Metal Corner Bead Offset Outside Corner (B1 OS) Designed for 135° corners. Offset bead is designed to give a true offset corner with a smaller bead height requiring less compound to finish. Can be used on any thickness of wallboard.

Standard lengths: 8′, 9′, 10′. Meets ASTM C1047.



Dimensions

Style	A	В	С	D
B1 OS	5/8"	3/4"	1/2"	5/8"

Note: OS = Offset



90° AND OFFSET INSIDE CORNER

USG Sheetrock* Brand Paper-Faced Metal Corner Trim Inside Corner (B2) Designed to form a true inside (90°) corner. For use with any thickness of wallboard. Standard lengths: 8′, 10′. Meets ASTM C1047.




Dimension

Style	A	В	С	D
B2	5/8"	3/8"	3/8"	5/8"




USG Sheetrock* Brand Paper-Faced Metal Corner Trim Offset Inside Corner (B2 OS) Designed for a 135° offset angle on inside corners greater than 90°. For use on any thickness of wallboard. Standard lengths: 8', 10'.



Dimensions

Style	A	В	С	D
B2 OS	5/8"	5/8"	5/8"	5/8"

Note: OS = Offset




SOFTLINE BULLNOSE AND OFFSET **OUTSIDE CORNER BEAD**

USG Sheetrock® Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Outside Corner (SLOC)

Installs easily to form a smooth rounded outside corner. The 3/4" radius can be used for 1/2" or 5/8" drywall. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

Dimensions



Style	A	Radius	В
SLOC	5/8"	3/4"	5/8"

3/4" Radius

USG Sheetrock® Brand Paper-Faced Metal Corner Bead 1" Bullnose Offset Outside Corner (SLOC OS)


Designed for 135° offset angles. Speeds application and eliminates need on framing members for fastening corners. Standard lengths: 8', 9', 10'. Meets ASTM C1047.

Dimensions



Style	A	Radius	В
SLOC OS	3/4"	1"	3/4"


Note: OS = Offset



USG Sheetrock® Brand Paper-Faced Metal Corner Bead 1/2" Bullnose Outside Corner (Baby Bull*)

 $Provides\, a\, narrower\, finished\, look\, with\, a\, smaller\, radius\, compared\, to\, other\, bullnose\, profiles.$ Also excellent for trimming around windows. Can be applied over new 1/2" or 5/8" drywall. Standard lengths: 8', 10'. Meets ASTM C1047.

Dimensions



Style	A	Radius	В
Baby Bull®	5/8"	1/2"	5/8"



SOFTLINE BULLNOSE AND OFFSET INSIDE CORNERS

USG Sheetrock® Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Inside Corner (SLIC)

Use to create a smooth, rounded inside corner. The 3/4" radius trim is suitable for 1/2" or 5/8" drywall. Standard lengths: 8', 10'. Meets ASTM C1047.

Dimensions



Style	A	Radius	В
SLIC	3/4"	3/4"	3/4"



L-TRIMS

USG Sheetrock® Brand Paper-Faced Metal Trim "L" Shaped (B4)

Use where wallboard abuts with suspended ceilings, beams, plaster, masonry and concrete walls, as well as untrimmed door and window jambs.

Standard lengths: 8', 10'. Meets ASTM C1047, with the exception of B4 (1/2").




Style	A	В	С
B4 (1/2")	1/2"	15/16"	1-5/16"
B4 (5/8")	5/8"	13/16"	1-5/16"



TAPE-ON FLEXIBLE OUTSIDE AND INSIDE CORNER BEAD


USG Sheetrock® Brand B1 Flexible Metal Corner, Tape-On Outside Flexible Corner (B1 Beaded Flex)

Proprietary style designed specifically to make straight, strong outside corner angles. Available in 3" width and manufactured with two 3/4" galvanized steel strips laminated to paper tape with a flexible gap between the strips. B1 Beaded Flex has a unique raised bead (nose) in the flexible gap to provide faster, easier finishing with drywall compound. For use on any wallboard thickness. Standard lengths: 8', 9', 10'. Meets ASTM C1047.



Dimensions

Style	A	В	С	D
B1 Beaded Flex (3")	11/16"	3/4"	3/4"	11/16"



PRODUCT SPOTLIGHT

USG SHEETROCK® BRAND PAPER-FACED METAL CORNER BEAD AND TRIM

- Fast, easy installation means reduced labour costs
- Provides superior resistance to edge cracking and eliminates costly job callbacks
- Apply with drywall compound—no nails to pop when wood framing shrinks
- Excellent for use with setting-type compounds for quicker finishing and decoration
- Unique "nose coating" on paper tape covering resists scuffing and fuzzing
- · Available in a variety of profiles
- Lifetime warranty against edge cracking

For a comprehensive description of the Lifetime Warranty, visit cgcinc.com



CGC Strait-Flex®

DRYWALL CORNER FLEX TAPE

COMPOSITE DRYWALL TAPES

CGC Strait-Flex® Drywall Corner Flex Tapes form easily to all angles and corners. Will not shrink, blister, tear, sag or wrinkle. Water-resistant and rustproof. Material can be second coated immediately. Does not require fasteners, stapling or any special tools. Slotted edges ensure superior bond.


CGC Strait-Flex® Original Composite Drywall Tape



Inside and outside corner flex tape designed to be the most versatile, multi-purpose drywall tape available. It allows you to create perfect inside and outside 90-degree and angled corners making it ideal for bay windows, coffered ceilings and inside corners where gaps are present. It will install using only half the compound compared to a conventional bead. Available in 100' rolls; 2-3/8" (6 cm) wide.

Dimensions

Style	A	В
Original	1-3/16"	1-3/16"



CGC Strait-Flex* Medium Composite Drywall Tape



Inside corner flex tape allows you to create perfect inside 90-degree corners, angled corners and inside angles of bay windows. Use it to straighten minor framing irregularities to produce straight, strong and professional inside corners. Available in 100' rolls; 2-1/4" (5.7 cm) wide.

Dimensions

Style	A	В
Medium	1-1/8"	1-1/8"



PAPER-FACED COMPOSITE DRYWALL TAPES CGC Strait-Flex® Paper-Faced Composite Drywall Tapes have a memory-free hinge design which allows for ease of installation, straighter corners and perfect angles. Straightens framing irregularities.


CGC Strait-Flex* Perfect* 90 Paper-Faced Composite Drywall Tape



A paper-faced laminated drywall tape ideal for inside corners. The paper edging allows for easier feathering and prevents edge cracking. The diamond-punched paper ensures ultimate bonding and faster drying while the laminated nose protects against fuzz-ups during finishing and sanding. Available in 25' rolls; 2-1/16" (5.2 cm) wide.

Dimension

Style	A	В	С	D
Perfect 90	5/16"	11/16"	11/16"	5/16"




CGC Strait-Flex* Mid-Flex 250 Paper-Faced Composite Drywall Tape



Ideal for inside, outside and angled corners. With its memory-free hinge design it speeds installation and allows you to create straight corners where framing irregularities may exist. The paper edging allows for easier feathering and prevents edge cracking. The diamond-punched paper ensures ultimate bonding and faster drying while the laminated nose protects against fuzz-ups during finishing and sanding. Available in 100' rolls; 2-1/2" (6.3 cm) wide.

Dimensions

Style	A	В	С	D
Mid-Flex 250	7/16"	13/16"	13/16"	7/16"




PAPER-FACED COMPOSITE **DRYWALL TAPES** (CONTINUED) CGC Strait-Flex® Mid-Flex 300 Paper-Faced Composite Drywall Tape



Ideal for inside, outside and angled corners. With its memory-free hinge design it speeds up installation and allows you to create straight corners where framing irregularities may exist. The paper edging allows for easier feathering and prevents edge cracking. The diamond-punched paper ensures ultimate bonding and faster drying time. Available in 100' rolls; 3" (7.6 cm) wide.

Dimensions

Style	A	В	С	D
Mid-Flex 300	1/2"	1"	1"	1/2"



CGC Strait-Flex® Wide-Flex 400 Paper-Faced Composite Drywall Tape




Designed for off angles and 90-degree corners with large framing irregularities and gaps. This product is ideal for hard-to-straighten vaults and outside corners, butterfly vaults, obtuse angles and double 5/8" outside corners. Use it to straighten framing irregularities and replace damaged metal corner bead. Available in 100' rolls: 4" (10.2 cm) wide.

Dimensions

Style	A	В	С	D
Wide-Flex 400	1/2"	1-1/2"	1-1/2"	1/2"


 $Designed\ to\ eliminate\ flat\ spots\ in\ curved\ applications\ making\ it\ the\ perfect\ solution\ for\ free-line and the perfect\ solution\ for\ free-line and\ f$

 $form, custom \ drywall \ applications \ where \ a \ seamless \ installation \ is \ required. \ The \ tear \ strips \ reduce$



COMPOSITE **CORNER BEAD**

CGC Strait-Flex® Arch-Stick **Arched Corner Bead**





	Dimensions	
Style	A	В
Arch-Stick	1-5/8"	1-5/8"



PRODUCT SPOTLIGHT

CGC STRAIT-FLEX® ARCH STICK

Designed to eliminate flat spots in curved corner applications.

- · Ideal for arched doors and windows, curved walls, ceilings, staircases and free-form custom drywall applications where a seamless installation is required
- PVC/Tempered-steel backbone for perfect arches; no flat spots
- Tear strips reduce transportation damage and are designed to make curved to straight transitions unnoticeable
- Composite nose resists dents and provides a beautiful corner without fuzz-up during finishing and sanding
- Easily installs using standard drywall compound, no special tools or fasteners required
- Second coat of compound can be applied immediately, very light skim-coat to finish



SURFACING SOLUTIONS

CGC offers a variety of textures and finishes to hide minor surface blemishes and provide distinctive interior styling. These products are fast, easy to apply and guick drying, saving labour time to preserve job profits.

Interior Texture Finishes

CGC textures provide an economical interior wall and ceiling solution for a wide range of patterns.

POWDER TEXTURE

CGC Sheetrock® Brand Medium Texture Finish™ Spray Texture



- · For decorating most interior ceilings
- · Provides attractive sand-finish texture
- · Hides minor surface defects
- · Available in: 20 kg bag

A polystyrene-aggregated spray coating for use over interior, above-grade drywall, plaster and concrete ceilings. Provides an attractive sand-finish appearance that helps conceal minor surface defects. Dries to a white finish that is often left unpainted but may be spray painted if preferred. Not washable unpainted.

READY-MIXED TEXTURE

CGC Sheetrock® Brand Ready-Tex® Spray Texture



- · Spray texture with ready-mixed convenience
- For decorating most interior walls and ceilings
- Provides attractive spatter/knockdown pattern
- · Dries to pure white finish
- · Available in: 16 L carton

A ready-mixed coating for use over interior, above-grade drywall, concrete and most other wall and ceiling surfaces. Formulated to create spatter/knockdown or orange peel texture patterns. Dries to a white finish that should be overpainted when dry. Not washable unpainted.

Plaster Finishes

VENEER PLASTER FINISHES AND BASECOATS

USG veneer plaster systems offer the opportunity to trim days from interior finishing schedules and provide strong, highly abrasion-resistant surfaces. These products are designed for one- or two-coat work over gypsum bases or directly to concrete block or properly prepared monolithic concrete. Both one- or two-coat applications offer a truly monolithic surface that is superior for critical light conditions.

VENEER FINISHES

USG Diamond® Veneer Finish



- · For economical, abrasion-resistant walls and ceilings
- · Excellent for texturing
- · Finish coat for one- and two-coat veneer plaster systems
- · Fast drying-permits next-day decorating
- Available in: 22.6 kg (50 lb.) bag

For application over CGC Grand Prix® Brand Veneer Plaster Base, USG Diamond® Brand and Imperial® Brand Veneer Basecoat and USG Red Top® Brand Gypsum Plaster Basecoats. Do not apply to completely dry basecoats. Apply USG Brand Plaster Accelerator Alum Catalyst solution to sun-faded CGC Grand Prix® Veneer Plaster Base. For interior use only.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

USG Imperial® Veneer Finish



- · For strong, abrasion-resistant interior finishes
- Durable and stable, especially in high-traffic areas
- · Usually ready for next-day decoration with a latex-based breather-type paint
- · When used with CGC Grand Prix® Brand Veneer Plaster Base, provides fire
- Available in: 22.6 kg (50 lb.) bag

For application over CGC Grand Prix® Brand Veneer Plaster Base and USG Imperial® Brand Veneer Basecoat Plaster. As finish coat over USG Diamond® Brand Veneer Basecoat applied to USG Durock™ Brand Cement Board or USG Fiberock® Brand Abuse-Resistant Panels. For interior use only.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

VENEER BASECOATS

USG Diamond® Veneer Basecoat




- · For economical two-coat residential and light-commercial applications
- Superior workability for faster, easier application
- Excellent base for a variety of plaster
- High coverage—as much as 4,000 to 5,000 sq. ft. per ton
- Available in: 22.6 kg (50 lb.) bag

Produces a monolithic base with regulated suction for constructing quality walls and ceilings in locations where the superior strength of USG Imperial® Basecoat Plaster may not be required.

For application over CGC Grand Prix® Brand Veneer Plaster Base, concrete block and monolithic concrete (treated with USG Plaster Bonder). For interior use only.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

USG Imperial® Veneer Basecoat



- Durable and stable, especially in high-traffic areas
- Permanent bond
- · When used with CGC Grand Prix® Brand Veneer Plaster Base, provides fire resistance
- · Available in: 22.6 kg (50 lb.) bag

High-strength, veneer plaster produces a hard, abrasion-resistant surface for commercial and residential applications where walls are exposed to significant traffic.

For application directly over CGC Grand Prix® Brand Veneer Plaster Base and concrete block. Treat monolithic concrete with USG Plaster Bonder before applying basecoat. For interior use only.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CONVENTIONAL **PLASTER FINISHES** AND BASECOATS

USG conventional plaster systems provide the highest-quality finish and the capability to create complex high-end surfaces such as vaults, domes and columns. These products feature excellent acoustical performance, proven fire resistance, increased abuse resistance and design flexibility, and are the best system to attain a uniform, monolithic, blemish-free, smooth surface with excellent wear resistance.

CONVENTIONAL **FINISHES**

CGC Red Top® Brand Gauging Plaster: Quick Set



- Plaster of Paris for moulding and casting when mixed with water alone
- · Mixes smoothly and easily
- · Provides smooth-trowel or sand-float lime-putty finishes for normal interior walls and ceilings
- Produces hard, crack and abrasionresistant surfaces
- Available in: 22.6 kg (50 lb.) bag

Mix with lime putty to create smooth-trowel and sand-float finishes over any gypsum basecoat. Type N (e.g. CGC Red Top® Single-Hydrate Finish Lime) or Type S (e.g. CGC Snowdrift® Double-Hydrate Finish Lime) recommended. Also for moulding and casting. For interior use only.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

USG Red Top® Brand Gauging Plaster: Slow Set



- Mixes smoothly and easily
- · Provides smooth-trowel or sand-float lime-putty finishes for normal interior walls and ceilings
- · Produces hard, crack and abrasionresistant surfaces
- · Available in: 22.6 kg (50 lb.) bag

Mix with lime putty to create smooth-trowel and sand-float finishes over any gypsum basecoat. Type N (e.g. CGC Red Top® Single-Hydrate Finish Lime) or Type S (e.g. CGC Snowdrift® Double-Hydrate Finish Lime) recommended. For interior use only

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CONVENTIONAL **BASECOATS**

USG Structo-Lite® Basecoat Plaster



- Mill-mixed perlite-aggregate gypsum plaster; requires only the addition of water at the jobsite
- Ideal where it is not desirable to mix aggregate with plaster on the jobsite
- Lightweight plaster; weighs less than half as much as sanded plaster
- Excellent for areas requiring highly insulated plaster
- Available in: 22.6 kg (50 lb.) bag

For application over gypsum lath, metal lath and masonry surfaces. Recommended over metal lath for float or texture finish only, not smooth-trowel finish. For interior use only.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

USG Red Top® Brand Gypsum Plaster



- Multipurpose conventional basecoat plaster applications
- The most popular conventional gypsum basecoat plaster in the building industry
- For hand or machine application; for use with sand or lightweight aggregates
- For plaster wall and ceiling assemblies requiring high fire-resistant and soundisolating performance
- Available in: 22.6 kg (50 lb.) bag

Mix with aggregate and apply to all standard lath and masonry plaster bases. Hand or machine apply. For interior use only.

GREENGUARD Gold certified and qualifies as a low VOC emitting material

Plaster Accessories

When conditions exist that affect the adhesion or the normal setting time of conventional plasters, veneer plasters, lime finish plasters and setting-type drywall compounds, CGC offers special additives in a variety of highperformance formulations.

USG Gypsum Plaster Retarder: Standard Strength and For Lime-Based Products



- For slowing the setting time of conventional plasters, veneer plasters, lime finish plasters and setting-type drywall compounds
- Available in the following formulations: Standard Strength and For Lime-Based Products
- Available in: 1.1 kg (2.5 lb.) resealable pouch (Standard Strength), 1.3 kg (3 lb.) resealable pouch (For Lime-Based Products)

USG Gypsum Plaster Retarders are additives that lengthen the setting time of gypsum plaster by slowing the chemical crystal formation that causes the gypsum plaster to set or harden. It easily disperses into mixing water for quick addition to plaster mix.

USG Gypsum Plaster Accelerator: Standard Strength



- For reducing the setting time of plasters and setting-type drywall compounds
- Easy to use
- Available in: 1.3 kg (3 lb.) resealable

Standard Strength is intended to provide a slight adjustment (10 to 30 minutes) to the setting time for veneer and conventional plasters.

USG Plaster Bonder



- Compatible with a large assortment of gypsum- and cement-based plasters
- Easily applied by brush, roller or spray to a uniform continuous film
- Tinted (pink) to allow easy visual inspection when required
- Film dries quickly for sameday use, or may be left unplastered for up to 10 days
- Available in: 3.7 L (1 gal.) resealable container

For bonding new plaster to gypsum plaster. cinder block, stone, drywall and other similar interior materials. Pink liquid dries to a light red coloured film that rewets when plaster is applied to provide an integral, strong, durable bond. Do not use around extremely moist or humid area such as swimming pools and do not apply to the underside of concrete roof decks.

PREPARATION SOLUTIONS

Proper preparation is essential for producing the best possible painted finish. Also important for a superior paint job is the equalization of both the porosity and surface texture to minimize decorating problems. CGC preparation solutions ensure your interiors are perfectly smooth and free of pockmarks, fine ridges and scuffed paper from sanding, providing a solid foundation for a superior finish.

Primers

Whether you're skim coating an entire surface or spray applying a primer, CGC primer and primer-surfacer minimize decorating problems and help achieve a superior paint job over interior gypsum board, wood and concrete surfaces.

CGC Sheetrock® Brand First Coat™ Drywall Primer



- · Ideal primecoat for interior gypsum board and concrete surfaces
- · Equalizes surface absorption and texture variations of substrate to minimize decorating problems
- · Apply with brush, roller or spray
- Dries white in less than 30 minutes top coat in an hour
- Available in: 20 L pail

Minimizes drywall decorating problems caused by porosity and surface texture variations between drywall face paper and areas finished with drywall compound. Also for use over new interior concrete and plaster finishes. Not a sealer or vapor barrier. Not intended as a final coating; paint or texture when dry.

USG Sheetrock® Brand Tuff-Hide™ Primer-Surfacer



- Achieves a Level 5 finish faster
- High build spray for a smoother, more beautiful finish
- Durable coating hides minor surface defects
- Excellent for critical light areas
- · Ideal finish for ceilings
- Dries white, can be tinted to match final top coat
- Available in: 18.9 L (5 gal.)

Provides a dual-purpose latex based coating for application over interior drywall. To achieve a GA-214/ASTM C840 Level 5 drywall finish, a single spray application provides the same highest quality finish as the traditional two step process of skim coating surfaces with drywall compound, followed by a coat of primer. Dries to a flat, white finish that can be left unpainted on noncontact surfaces, such as ceilings.

INTERIOR PATCH & REPAIR SOLUTIONS

Finished interior walls are subject to abuse and damage from time to time. CGC offers a line of repair products to deal with a variety of holes, cracks, dents and abrasions.

Repair Products

CGC Sheetrock® Brand Dust Control® Patch & Repair Kit



- Unique formula binds up fine residue during sanding to form heavier particles that tend to fall to the floor instead of clouding the air
- Kit includes: 236 mL pail of compound. 4" x 4" metal patch, compound applicator, and 2 drywall sanding pads

Reduces airborne sanding dust for faster clean-up—ideal for remodeling projects. Kit includes everything needed to repair small to medium sized drywall damage.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand Dust Control® Tube with Applicator Cap



- · For repairing small holes and cracks in drywall
- Available in: 162 mL tube

Reduces airborne sanding dust for faster clean-up—ideal for remodeling projects. Suitable for filling nail holes and other small repairs. Unique cap designed to be used as a tool to smooth compound when applied.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand Setting-Type Drywall Compound



- Available in 5-, 20- and 90-minute
- For one-day patching and joint finishing and next-day decoration
- Easy to sand
- Provides low shrinkage and a superior
- Available in: 1.25 kg resealable pouch

For patching small holes and cracks in interior drywall and plaster surfaces, and filling and levelling interior above-grade concrete walls and ceilings. For taping and finishing joints in interior drywall.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand Durabond® Setting-Type Drywall Compound



- · Available in 90-minute set time
- Exceptional bond with low shrinkage
- Same-day finishing and next-day decorating possible
- Excellent check-crack resistance in heavy fills
- Unique resistance to humidity
- Available in: 2 kg resealable pouch

For patching small holes and cracks in interior drywall and plaster surfaces, and filling and levelling interior above-grade concrete walls and ceilings. For taping joints in interior $% \left(1\right) =\left(1\right) \left(1\right) \left($ drvwall.

GREENGUARD Gold certified and qualifies as a low VOC emitting material.

CGC Sheetrock® Brand Drywall Repair Clips



- For fast, easy drywall repair of large holes (over 2") and areas damaged by water
- When used with fire-rated drywall, meets building code requirements for repairing one-hour fire-rated drywall partitions
- Suitable for both 1/2" and 5/8" drywall
- 6 clips, 12 drywall screws

CGC Strait-Flex® Perma-Patch Drywall Repair Patch



- Quickly repairs door knob damage to drywall
- Imprinted with can light and standard receptacle patterns for easy trimming
- The most economical and permanent way to repair drywall
- Outperforms metal patches
- Available in: 8" x 8" patch, 2-pack

CGC Strait-Flex® Outlet Patch Receptacle Repair Patch



- Pre-cut to fit standard receptacle boxes
- Repairs and reinforces mis-cuts or damaged areas around receptacle box
- · Very fast, extremely strong
- Available in: 4-3/4" x 6-1/4" patch, 2-pack

CGC Wall Repair Patches



- Ideal for patching holes in drywall and plaster
- Self adhesive
- · Metal reinforced
- Available in: 4" x 4", 6"x 6"

QUICK REFERENCE GUIDES

DRYWALL COMPOUND **APPLICATION GUIDE**

		Page#	Embedding Tape/Bead	Filling	Finishing	Crack Repair	Hole Repair	Minimum Time Before Reapplying*
	CGC Sheetrock® All Purpose	4						24 hrs.
	CGC Sheetrock® All Purpose Lite	4					-	24 hrs.
DNUC	CGC Sheetrock® Machine Mud®	4					-	24 hrs.
READY-MIXED DRYWALL COMPOUND	CGC Sheetrock® X-Tra Lite™	4	-				-	24 hrs.
READY WALL	CGC Sheetrock® Lite-Weight Taping	5					-	24 hrs.
DRY	CGC Sheetrock® Total™	5					-	24 hrs.
	CGC Sheetrock® Dust Control®	5					-	24 hrs.
	CGC Sheetrock® UltraLight	5					-	24 hrs.
	CGC Sheetrock® 5	6		-	-		-	5 mins.
* * QN	CGC Sheetrock® 20	6			-		-	20 mins.
3-TYPE	CGC Sheetrock® 45	6			-		-	45 mins.
SETTING-TYPE DRYWALL COMPOUND*	CGC Sheetrock* 90	6			-		_	90 mins.
S	CGC Durabond® 45	6		-	-			45 mins.
	CGC Durabond® 90	6		-	-			90 mins.

^{*} Drying time is dependant on the environment's temperature and humidity levels. At 24 °C (75 °F), 50% R.H., allow approx. 24 hours for compound to dry.

CGC STRAIT-FLEX® APPLICATION GUIDE

		Page #	Outside 90° Corners	Inside 90° Corners	Angled Corners	Vaults
OSITE WALL PE	CGC Strait-Flex* Original	11				
COMPOS DRYWA TAPE	CGC Strait-Flex® Medium	11	-			-
ш	CGC Strait-Flex® Perfect 90	11	-			-
-FACED OSITE ILL TAPI	CGC Strait-Flex® Mid-Flex 250	11				
APER COMP	CGC Strait-Flex® Mid-Flex 300	12				
	CGC Strait-Flex® Mid-Flex 400	12		-		

RECOMMENDED ACCEPTABLE - NOT RECOMMENDED

Setting time is a range that can be affected by temperature, relative humidity and wet-thickness. Application to porous surface or at less than 3 mm (1/8 in.) thickness may prevent chemical setting and bond. Paint should only be applied once compound is dry.

CGC COMMODITY CODES

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Palle
CGC Sheetrock® Brand All Purpose Drywall Compound	16 L carton	381501	-	48
CGC Sheetrock® Brand All Purpose Drywall Compound	12 L pail	381420	-	64
CGC Sheetrock® Brand All Purpose Drywall Compound	4.5 L pail	381422	-	96
CGC Sheetrock® Brand All Purpose Drywall Compound	2 L pail	381413	6	48 cartons
CGC Sheetrock® Brand All Purpose Lite Drywall Compound	17 L carton	380114	-	48
CGC Sheetrock® Brand All Purpose Lite Drywall Compound, Beige	17 L carton	381650	-	48
CGC Sheetrock® Brand Machine Mud® Drywall Compound	17 L carton	380002	-	48
CGC Sheetrock® Brand X-tra Lite™ Drywall Compound	17 L carton	381470	-	48
CGC Sheetrock® Brand Lite-Weight Taping Drywall Compound	17 L carton	380157	-	48
CGC Sheetrock® Brand Total™ Drywall Compound	17 L carton	381652	-	48
CGC Sheetrock® Brand Dust Control® Drywall Compound	17 L carton	380230	-	48
CGC Sheetrock® Brand Dust Control® Drywall Compound	12 L pail	380163	-	64
CGC Sheetrock® Brand Dust Control® Drywall Compound	4.5 L pail	380550	-	96
CGC Sheetrock® Brand Dust Control® Drywall Compound	2 L pail	380521	6	48 cartons
CGC Sheetrock® Brand UltraLight Drywall Compound	11.5 L pail	380155	-	64

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
CGC Sheetrock® Brand 90 Setting-Type Drywall Compound	11 kg bag	381419	-	96
CGC Sheetrock® Brand 90 Setting-Type Drywall Compound	1.25 kg pouch	380383	6	90 cartons
CGC Sheetrock® Brand 45 Setting-Type Drywall Compound	11 kg bag	381100	-	96
CGC Sheetrock® Brand 20 Setting-Type Drywall Compound	11 kg bag	381108	-	96
CGC Sheetrock® Brand 20 Setting-Type Drywall Compound	1.25 kg pouch	380384	6	90 cartons
CGC Sheetrock® Brand 5 Setting-Type Drywall Compound	11 kg bag	381120	-	96
CGC Sheetrock® Brand 5 Setting-Type Drywall Compound	1.25 kg pouch	380395	6	90 cartons
CGC Sheetrock® Brand Durabond® 90 Setting-Type Drywall Compound	15 kg bag	381600	-	80
GC Sheetrock® Brand Durabond® 90 Setting-Type Drywall Compound	2 kg pouch	380381	6	90 cartons
GC Sheetrock® Brand Durabond® 45 Setting-Type Drywall Compound	15 kg bag	381330	-	80

CONCRETE LEVELLING COMPOUNDS				
Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
CGC Sheetrock® Brand Cover Coat® Levelling Compound	15 kg bag	380322	-	60

JOINT TAPES				
Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
CGC Sheetrock® Brand Paper Joint Tape	75' roll; 2-1/16" wide	380045	24	100 cartons
CGC Sheetrock® Brand Paper Joint Tape	250' roll; 2-1/16" wide	381405	20	36 cartons
CGC Sheetrock® Brand Paper Joint Tape	500' roll; 2-1/16" wide	381410	10	40 cartons
Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
CGC Sheetrock® Brand Fiberglass Joint Tape	65' roll; 2" wide	380012	24	75 cartons

300' roll; 2" wide

500' roll; 2" wide

300' roll; 2" wide

300' roll; 2-1/2" wide

380009

380008

380018

12

12

12

FIBERGLASS JOINT

 $\mathsf{CGC}\,\mathsf{Sheetrock}^{\circledast}\,\mathsf{Brand}\,\mathsf{Fiberglass}\,\mathsf{Joint}\,\mathsf{Tape}$

USG Imperial® Brand Tape: Type P

CGC Sheetrock® Brand Fiberglass Joint Tape

CGC Sheetrock® Brand Mould-Resistant Fiberglass Joint Tape

PAPER JOINT TAPES

63 cartons

60 cartons

63 cartons

54 cartons

	BEAD AND TRIM				
90° AND OFFSET	Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pall
SIDE CORNER BEAD	USG Sheetrock* Brand Paper-Faced Metal Corner Bead Outside Corner (B1W)	7', 8', 9', 10'	280380	50	60 cartons
	USG Sheetrock* Brand Paper-Faced Metal Corner Bead Outside Corner (B1XW EL)	7', 8', 9', 10', 12'	280350	50	60 cartons
	USG Sheetrock* Brand Paper-Faced Metal Corner Bead Outside Corner (B1 Super Wide)	8',10'	280460	50	60 cartons
	USG Sheetrock* Brand Paper-Faced Metal Corner Bead Offset Outside Corner (B1 OS)	8', 9', 10'	280270	50	60 cartons
90° AND OFFSET	Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pal
INSIDE CORNER	USG Sheetrock* Brand Paper-Faced Metal Corner Trim Inside Corner (B2)	8',10'	281530	50	60 cartons
	USG Sheetrock* Brand Paper-Faced Metal Corner Trim Offset Inside Corner (B2 OS)	8', 10'	281520	50	60 cartons
FTLINE BULLNOSE	Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pal
AND OFFSET OUTSIDE CORNER BEAD	USG Sheetrock* Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Outside Corner (SLOC)	8', 9', 10'	280320	50	60 cartons
	USG Sheetrock® Brand Paper-Faced Metal Corner Bead 1″ Bullnose Offset Outside Corner (SLOC OS)	8', 9', 10'	280310	50	60 cartons
	USG Sheetrock* Brand Paper-Faced Metal Corner Bead 1/2" Bullnose Outside Corner (Baby Bull*)	8', 10'	280260	50	60 cartons
OFTLINE BULLNOSE	Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pa
ND OFFSET INSIDE CORNERS	USG Sheetrock® Brand Paper-Faced Metal Corner Bead 3/4" Bullnose Inside Corner (SLIC)	8',10'	281510	50	60 cartons
L-TRIMS	Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pal
	USG Sheetrock® Brand Paper-Faced Metal Trim "L" Shaped (B41/2")	8',10'	281490	50	60 cartons
	USG Sheetrock* Brand Paper-Faced Metal Trim "L" Shaped (B4 5/8")	8',10'	281480	50	60 cartons
TAPE-ON FLEXIBLE	Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pa
JTSIDE AND INSIDE CORNER BEAD	USG Sheetrock® Brand B1 Flexible Metal Corner (B1 Beaded Flex)	8',10'	280430	50	60 cartons
COMMENDEAD	CGC Strait-Flex® Perfect 90 Paper-Faced Composite Drywall Tape	25' roll; 2-1/16" wide	681176	12	48 cartons
	CGC Strait-Flex® Original Composite Drywall Tape	100' roll; 2-3/8" wide	681115	12	24 cartons
	CGC Strait-Flex® Medium Composite Drywall Tape	100' roll; 2-1/4" wide	681135	12	24 cartons
	CGC Strait-Flex® Mid-Flex 250 Paper-Faced Composite Drywall Tape	100' roll; 2-1/2" wide	681130	10	24 cartons
	CGC Strait-Flex® Mid-Flex 300 Paper-Faced Composite Drywall Tape	100' roll; 3" wide	681120	10	24 cartons
	CGC Strait-Flex® Wide-Flex 400 Paper-Faced Composite Drywall Tape	100' roll; 4" wide	681125	7	24 cartons
	CGC Strait-Flex® Arch-Stick Composite Corner Bead	10'	285735	25	48 cartons

INTERIOR TEXTURE FINISHES							
Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet			
CGC Sheetrock® Brand Medium Texture Finish™ Spray Texture	20 kg bag	540154	-	60			
Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet			
CGC Sheetrock® Brand Ready-Tex® Spray Texture	16 L carton	380015	-	48			

READY-MIXED TEXTURE

POWDER TEXTURE

VENEER FINISHES

VENEER BASECOATS

CONVENTIONAL FINISHES

CONVENTIONAL BASECOATS

FINISHING LIMES

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Diamond® Veneer Finish	22.6 kg (50 lb.) bag	162640	-	63
USG Imperial® Veneer Finish	22.6 kg (50 lb.) bag	164949	-	63
Product	Available In	Commodity Code	Quantity per Carton	Quantity per Palle
USG Diamond® Veneer Basecoat	22.6 kg (50 lb.) bag	162681	-	63
USG Imperial® Veneer Basecoat	22.6 kg (50 lb.) bag	164849	-	63
Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
CGC Red Top® Brand Gauging Plaster: Quick Set	22.6 kg (50 lb.) bag	163351	-	63
USG Red Top® Brand Gauging Plaster: Slow Set	22.6 kg (50 lb.) bag	163352	-	63
Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Structo-Lite® Basecoat Plaster	22.6 kg (50 lb.) bag	163841	-	40
USG Red Top® Brand Gypsum Plaster	22.6 kg (50 lb.) bag	163840	-	63
Product	Available In	Commodity Code	Quantity per Carton	Quantity per Palle
				<u> </u>
CGC Red Top® Single Hydrated (Type N)	22.6 kg (50 lb.) bag	401460	-	50

PLASTER ACCESSORIES

CGC Snowdrift® Double Hydrated (Type S)

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
USG Gypsum Plaster Retarder: Standard Strength	1.1 kg resealable pouch	160217	6	48 cartons
USG Gypsum Plaster Retarder: For Lime-Based Products	1.3 kg resealable pouch	160218	6	48 cartons
USG Gypsum Plaster Accelerator: Standard Strength	1.3 kg resealable pouch	160216	6	48 cartons
USG Plaster Bonder: Pink	3.7 L container	161200	6	36 cartons

22.6 kg (50 lb.) bag

409240

PRIMERS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
CGC Sheetrock® Brand First Coat™ Drywall Primer	20 L pail	544819	-	48
USG Sheetrock® Brand Tuff-Hide™ Primer-Surfacer	18.9 L (5 gal.) pail	542728	-	48

REPAIR PRODUCTS

Product	Available In	Commodity Code	Quantity per Carton	Quantity per Pallet
CGC Sheetrock® Brand Drywall Repair Clips	6 clips, 12 drywall screws	385001	20 packs	-
CGC Sheetrock® Brand Dust Control® Patch and Repair Kit	5-piece kit	380149	6	108 cartons
CGC Sheetrock® Brand Dust Control® Tube with Applicator Cap	162 mL tube	380148	6	210 cartons
CGC Strait-Flex® Perma-Patch Drywall Repair Patch	8" x 8", 2-pack	380885	50	24 cartons
CGC Strait-Flex® Outlet Patch Receptacle Repair Patch	4-3/4" x 6-1/4", 2-pack	380445	50	24 cartons
CGC Wall Repair Patch	4" x 4"	380441	12	441 cartons
CGC Wall Repair Patch	6" x 6"	380661	12	225 cartons



GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage (CDPH Standard Method V1.1, also known as CA Section 01350). For more information, visit ul.com/gg.

50

		_
		_
		_
		_
		_
		_
		_
		_
		_
		_
		_
		_
		-
		_
		_
		-
		_
		_
		_
		_
		_
		_
		_
		_
		-
		_
		_

CONTACT INFORMATION

Manufactured by CGC Inc.

350 Burnhamthorpe Rd. W., 5th Floor Mississauga, ON L5B 3J1

United States Gypsum Company 550 West Adams Street Chicago, IL 60661

PRODUCT INFORMATION

See cgcinc.com for the most up-to-date product information.

CUSTOMER SERVICE

1.800.387.2690

WEBSITES

cgcinc.com cgcdesignstudio.com

Products described here may not be available in all geographic markets. Consult your CGC representative for information. The information in this document is subject to change without notice. USG Corporation assumes no responsibility for any errors that may inadvertently appear in

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety and industrial hygiene practices during handling and installation of all products and systems. Take necessary precautions and wear the appropriate personal protective equipment as needed. Read Safety Data Sheets and related literature on products before specification and/or installation.

