

Submittal Sheet

Submittal Sheet #0309047

Drywall Laminating Screw (232)

Product:		ltem#		Description 10 x 1-1/2-in, Bugle Head, Coarse Thread, Drywall Laminator, Type G, Phosphate, Collated					Unit Po	Unit Pack	
	C12 12								1,000		
				10 x 1-1/2-in, Bugle Head, Coarse Thread, Laminator, Phillips, Phosphate, 5,000 Bulk							
		12Z	10 Bul		, Bugle Head	l, Coarse 1	Thread, Lamii	nator, Phil	lips, Clear Z	inc, 5,000	
Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Grabber	Interior Wood	Bugle Head	0.19	0.343	#10-8	1.5	Grabber	1.375	N/A	N/A	P, RG
Applicatio	n:	GRABBER's of glueing or lo	lrywall lami aminating. (nating scre Not recom	ws are used mended for	for tempo double lay	rary attachme er 3/8-in par	ent of gyp nels)	sum board to	o gypsum bo	oard when
Applicatio	n:	GRABBER's o glueing or lo	Irywall lami aminating. (nating scre Not recom	ws are used mended for	for tempo double lay	rary attachme er 3/8-in par	ent of gyp nels)	sum board to	o gypsum bo	oard when
Descriptio							ar in mind! E Ite finish and			or additiona	l holding
Directions:		Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimum performance is 4 amps minimum and 0 to 4,000 rpm. Screw is completely seated when the head is flush with the work surface. Overdriving may result in failure of the fastener or stripping of the head recess. Do not overdrive.									
Certifications:		All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASTM C1002, as referenced in ICCES report ER-5280 are approved for use in structures governed by the International Building Code 2006, 2009, 2012, International Residential Building Code 2006, 2009, and 2012.									

ubmittal Sheet #0309047				
SUBMITTAL APPROVALS:				
JOB NAME				
CONTRACTOR	DATE			
TRADEMARKS:	NOTICE:			
The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.	We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.			

Submittal Sheet #0309047

Drywall Laminating Screw (232)



PRODUCT SPECIFICATIONS	
Fastener Classification	Interior Wood
Fastener Head	Bugle
Fastener Drive	#2 Phillips
Fastener Gauge	#10
Fastener Point	Grabber
Fastener Package Type	Packaged Screws, Collated Screws (for automated feed systems)
Fastener Package Weight	Mini Pack, 1lb Box, 5 Pound, Bulk Box
Fastener TPI	8
Fastener Coating	Black/Gray Phosphate, Gray Phosphate, Clear Zinc, GrabberGard

STANDARD CORROSION TEST RESULTS					
Finish	Test	Standard/Protocol	Results		
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust		
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust		
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust		
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust		
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust		
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust		
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust		
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust		

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.