

CONTINENTAL™
BUILDING PRODUCTS



Applications

Drywall is designed to be easy to use and decorate for both residential and commercial construction applications.

- Interior walls
- Interior ceilings

Advantages

- 25% lighter than standard 1/2" drywall
- Easier lifting and handling for fast installation
- Sag resistance
- Fire resistance
- Can be cost-effectively decorated numerous times
- 99% recycled content by weight
- Less jobsite waste
- Reduced transportation energy
- Low VOC-emitting materials
- Easy score and snap
- Reduced dust

LIGHTWEIGHT, GENERAL PURPOSE DRYWALL

LIFTLITE® DRYWALL

Continental Building Products LiftLite is a gypsum board formulated to be up to 25% lighter than standard 1/2" drywall making it easier to lift, carry and install. LiftLite can be used on both walls and ceilings, eliminating the need for two different types of drywall and reducing jobsite waste. Like all Continental interior gypsum boards, LiftLite is GREENGUARD Certified, which can assist in the attainment of credits for LEED certification.

LiftLite can be used in building applications that require direct mechanical attachment to wood or metal wall and ceiling frames, or attachment to existing surfaces using fasteners or adhesives. It has excellent sag resistance and may be used on ceilings with framing up to 24" o.c. with a water-based texture application when installed perpendicularly to the framing, meeting the requirements of Gypsum Ceiling Board. It can also be used on walls with framing up to 24" o.c.

While LiftLite has some inherent fire-resistant characteristics, this product should not be used to provide the levels of fire resistance required by various building codes and standards. For fire resistance, use Firecheck® products. When properly sealed and used in a certified sound rated assembly, LiftLite will contribute to required sound transmission classification (STC) values.

Note: LiftLite is suitable for interior applications only, and should not be used where temperatures exceed 125° F for extended periods or in areas of extreme humidity. Likewise, the board should be protected from exposure to adverse conditions during storage and construction.

JOB NAME:

CONTRACTOR:

DATE:

Sustainability

Can contribute to the U.S. Green Building Council's LEED Credit Qualification in several credit categories to assist in obtaining LEED certification.



*The federal specification for gypsum board, SS-L-30D, was withdrawn in 1984. It is provided here for information only and should not be referenced for new construction.

Physical Characteristics

Core: Non-combustible, dimensionally stable, inert gypsum

Paper: 100% recycled; Front and edges = ivory, back = gray

Long Edges: Tapered

Asbestos free and GREENGUARD certified

LEED and Recycled Content: 99% recycled content, 94% pre-consumer and 5% post-consumer

Standards and Codes

Formulated to perform in accordance with ASTM C1396/C1396M, Sections 5 & 12 and C36; Federal Specification SS-L-30D*, Type III, Grade R; and CAN/CSA-A82.27-M.

Technical Specifications

UL classified for surface burning (File No. R16102) (per ASTM E84 and CAN/ULC-S102) Flame spread = 0; Smoke developed = 0; Meeting IBC, Section 803.1, Class A

Core combustibility (tested in conformance with ASTM E136) Non-combustible

Installation

Install according to Gypsum Association GA-201, GA-216, or ASTM C840. Refer to GA-214 for finishing recommendations.

Painting and Decorating

For best results, a good gypsum board primer should be applied in accordance with manufacturer's instructions before painting or before any textured material is applied.

Handling Recommendations

Stack flat, keep dry and lift (do not drag) to avoid scuffing. Avoid damage to edges. For detailed recommendations, refer to GA-216 and GA-801.

Safety Precautions

Wear safety glasses and NIOSH-approved respirators during cutting, breaking, rasping or other dust-producing activities.

Material Safety Data Sheets (MSDS) are available for all Continental products upon request.

Available Sizes:

Nominal thickness 1/2 in.

Nominal width 4 ft.


Standard length † 8 ft., 10 ft., 12 ft.

Nominal width 54 in.

Standard length † 12 ft. and 14 ft.

Nominal weight 1.3 lbs./ft.² – 1.4 lbs./ft.²

†Other lengths available by special order



CONTINENTAL™

CONTINENTAL BUILDING PRODUCTS

USA (800) 237-5505

Canada (866) 649-7786

www.continental-bp.com

