SAFETY DATA SHEET

1. Identification

Product identifier CGC Sheetrock® Brand Total™ Drywall Compound

Other means of identification

SDS number 61001010021

Synonyms Joint Compound (Ready-Mixed), Taping Compound, Mud, Finishing Compound

Recommended use Interior use.

Recommended restrictions Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

CGC Inc. Company name

Address 350 Burnhamthorpe Road West, 5th Floor

> Mississauga, Ontario L5B 3J1 A Subsidiary of USG Corporation

Telephone 1-800-387-2690 Website www.cgcinc.com 1-800-507-8899 **Emergency phone number**

2. Hazard(s) identification

Physical hazards Not classified. **Health hazards** Not classified. **Environmental hazards** Not classified.

Label elements

None. Hazard symbol Signal word None. **Hazard statement** None.

Precautionary statements

Observe good industrial hygiene practices. Prevention Get medical attention/advice if you feel unwell. Response

Store as indicated in Section 7. Storage

Dispose of in accordance with federal, provincial and local regulations. **Disposal**

Other hazards None known. Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Perlite	93763-70-3	< 15
Kaolin	1332-58-7	< 10
Attapulgite	12174-11-7	< 5

All concentrations are in percent by weight unless ingredient is a gas. **Composition comments**

Raw materials in this product may contain respirable crystalline silica as an impurity. See Section

16 for further information.

4. First-aid measures

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move

injured person into fresh air and keep person calm under observation. Get medical attention if

symptoms persist.

Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or Skin contact

persists.

Eye contact Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical

assistance.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Under normal conditions of intended use, this material does not pose a risk to health. Dust may

irritate throat and respiratory system and cause coughing.

Provide general supportive measures and treat symptomatically.

Indication of immediate medical attention and special

treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials.

Not applicable.

Specific hazards arising from

the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in

case of fire.

Fire fighting

equipment/instructions

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods Cool material exposed to heat with water spray and remove it if no risk is involved.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, provincial, and federal regulations.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling Avoid inhalation of dust and contact with skin and eyes. Minimise dust generation and

accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe

good industrial hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a mouldy appearance or an unpleasant odour. Keep containers closed when not in use.

Filled cartons and pails of joint compound may be stacked a maximum of 3 layers high on a pallet. Pallets may only be stacked a maximum of two high.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)			

Components	Туре	Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form	
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable.	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form
Kaolin (CAS 1332-58-7)	TWA	2 mg/m3	Respirable fraction.
Perlite (CAS 93763-70-3)	TWA	10 mg/m3	

Canada. Quebec OELs. (Ministry of Labour - Regulation Respecting the Quality of the Work Environment)

Components	Туре	Value	Form
Attapulgite (CAS 12174-11-7)	TWA	1 fibers/cm3	Fiber.
Kaolin (CAS 1332-58-7)	TWA	5 mg/m3	Respirable dust.

Biological limit values No biological exposure limits noted for the ingredient(s).

Provide sufficient ventilation for operations causing dust formation. Observe occupational Appropriate engineering controls exposure limits and minimise the risk of exposure.

Individual protection measures, such as personal protective equipment

Wear approved safety goggles. Eye/face protection

Skin protection

It is a good industrial hygiene practice to minimise skin contact. For prolonged or repeated skin **Hand protection**

contact use suitable protective gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

> limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure air supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.

Thermal hazards None.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Semi-solid. Physical state **Form** Paste. Colour Off-white.

Odour Low to no odour. **Odour threshold** Not applicable. 9.5 - 9.9 pН Melting point/freezing point Not applicable. Initial boiling point and boiling Not applicable.

range

Flash point Not applicable. **Evaporation rate** Not applicable. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not applicable.

Flammability limit - upper

(%)

Not applicable.

Explosive limit - lower (%)

Explosive limit - upper

(%)

Not applicable. Not applicable.

Not applicable. Vapour pressure Not applicable. Vapour density Relative density 0.9 - 1 (H2O=1)

Solubility(ies)

Solubility (water) Soluble in water. Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable. **Decomposition temperature** Not applicable. **Viscosity** Not applicable.

Other information

0.9 - 1 kg/l **Bulk density** VOC (Weight %) 4 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Conditions to avoid None known. Incompatible materials None known.

Above 800°C (1472°F) limestone (CaCO3) can decompose to lime (CaO) and release carbon Hazardous decomposition

dioxide (CO2). products

11. Toxicological information

Information on likely routes of exposure

Airborne dust may irritate throat and upper respiratory system causing coughing. Inhalation

Skin contact May cause allergic skin reactions especially in individuals with pre-existing skin disease such as

eczema. (See Section 16).

Eye contact Airborne dust may cause mechanical eye irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing

Information on toxicological effects

Acute toxicity Not expected to be a hazard under normal conditions of intended use.

Components **Species Test results**

Kaolin (CAS 1332-58-7)

Acute

Dermal

LD50 Rat > 5000 mg/kg

Inhalation

Version #: 01

LC50 Rat > 2 mg/l, 4 Hours

Oral

933477

LD50 Rat > 5000 mg/kg

Issue date: 02-May-2016

CGC Sheetrock® Brand Total™ Drywall Compound

Revision date: -

SDS Canada

Skin corrosion/irritation Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation The product contains a small amount of sensitising substance which may provoke an allergic

reaction among sensitive individuals after repeated contact.

For detailed information, see section 16.

Germ cell mutagenicity Data does not suggest that this product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not expected to increase the risk of cancer.

ACGIH Carcinogens

Kaolin (CAS 1332-58-7) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

KAOLIN, RESPIRABLE FRACTION (CAS 1332-58-7) Not classifiable as a human carcinogen.

Canada - Quebec OELs: Carcinogen category

Attapulgite (CAS 12174-11-7) Detected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Attapulgite (CAS 12174-11-7) 2B Possibly carcinogenic to humans.

3 Not classifiable as to its carcinogenicity to humans.

Reproductive toxicity Not expected to be a reproductive hazard.

Specific target organ toxicity -

single exposure

No data available, but none expected.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged exposure may cause chronic effects. For detailed information, see section 16.

Further information No additional adverse health effects noted.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test results

Kaolin (CAS 1332-58-7)

Aquatic Acute

Crustacea LC50 Daphnia magna > 1.1 g/l, 48 Hours

Persistence and degradability N

No data available.

Bioaccumulative potential Bioaccumulation is not expected.

Mobility in soilNo data available.Other adverse effectsNone expected.

13. Disposal considerations

Disposal instructions Dispose of in accordance with federal, provincial and local regulations. Recycle responsibly.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to N Annex II of MARPOL 73/78 and

Not applicable.

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

16. Other information

Issue date 02-May-2016

Revision date - 01

Further information

Attapulgite: Carcinogenic to experimental animals via a route of exposure not relevant to human exposure per ACGIH.

Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is within the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with eczema.

Crystalline silica: Raw materials in this product may contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica in this product is < 0.1%. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

Bucket NFPA Classification:

Health: 0 Flammability: 1 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA ratings Health: 1

Flammability: 0 Instability: 0

CGC Sheetrock® Brand Total™ Drywall Compound

NFPA ratings



ACGIH: American Conference of Governmental Industrial Hygienists. List of abbreviations

NFPA: National Fire Protection Association.

RTECS: Registry of Toxic Effects of Chemical Substances. Registry of Toxic Effects of Chemical Substances (RTECS)

References

HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

Torben et al. (2001). Environmental and Health Assessment of Substances in Household

Detergents and Cosmetic Products.

Disclaimer This information is provided without warranty. The information is believed to be correct. This

information should be used to make an independent determination of the methods to safeguard

workers and the environment.

SDS Canada

933477 Version #: 01 Revision date: - Issue date: 02-May-2016