

**ACOUSTICAL SEALANT**Version 7.0  
REVISION DATE: 06/24/2014

Print Date 06/26/2014

**SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION****Product Information**

Trade name : ACOUSTICAL SEALANT

Product code : 93170X 333

Supplier : Tremco Canada division  
220 Wicksteed Avenue  
Toronto, ON M4H 1G7

Telephone : (416) 421-3300  
Emergency Phone : (613) 996-6666

Product use : Sealant

**Preparation Information**

Prepared by: : Sewnauth Raghunandan  
Date: : 06/24/2014  
Telephone : (416) 421-3300

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Dark Gray. Non-sag gunnable paste. No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : No serious effects anticipated under normal conditions of use. Vapor may irritate respiratory tract.

Eyes : Slightly irritating.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : Irritant effect may be delayed.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

## ACOUSTICAL SEALANT

Version 7.0  
REVISION DATE: 06/24/2014

Print Date 06/26/2014

### SECTION 3 : HAZARDOUS INGREDIENTS

Chemical Name	CAS-No.	Weight % Range
Stoddard solvent (Mineral Spirits)	8052-41-3	7.0 - 13.0
Petroleum distillates	64742-47-8	1.0 - 5.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0
Titanium dioxide	13463-67-7	0.1 - 1.0
1,2,4-Trimethylbenzene	95-63-6	0.1 - 1.0
Carbon Black	1333-86-4	0.1 - 1.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

### SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for 15 minutes. If irritation persists, get medical attention.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

### SECTION 5: FIRE / EXPLOSION HAZARDS

Flash point	:	Not available.
Method	:	Not available.
Burning rate	:	Non-flammable solid
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Smoke, fumes. Carbon monoxide and carbon dioxide can form.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

### SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal.



**ACOUSTICAL SEALANT**

Version 7.0  
 REVISION DATE: 06/24/2014

Print Date 06/26/2014

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Do not use in confined or poorly ventilated areas. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use. Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures** : General ventilation is sufficient.

**Exposure Limits**

<b>Chemical Name</b>	<b>CAS Number</b>	<b>Regulation</b>	<b>Limit</b>	<b>Form</b>
Stoddard solvent (Mineral Spirits)	8052-41-3	Ontario TWAEV: ACGIH TWA:	525 mg/m3 100 ppm	
Petroleum distillates	64742-47-8	Ontario TWAEV: Ontario TWAEV: ACGIH TWA: ACGIH TWA: ACGIH TWA:	525 mg/m3 200 mg/m3 200 mg/m3 200 mg/m3 200 mg/m3	as total hydrocarbon vapor Non-aerosol.as total hydrocarbon vapor Non-aerosol.as total hydrocarbon vapor
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	Ontario TWAEV: ACGIH TWA:	0.10 mg/m3 0.025 mg/m3	Respirable fraction. Respirable fraction.
Titanium dioxide	13463-67-7	Ontario TWAEV: ACGIH TWA:	10 mg/m3 10 mg/m3	Total dust.
1,2,4-Trimethylbenzene	95-63-6	Ontario TWAEV: ACGIH TWA:	123 mg/m3 25 ppm	
Carbon Black	1333-86-4	Ontario TWAEV: ACGIH TWA:	3.5 mg/m3 3.5 mg/m3	

**ACOUSTICAL SEALANT**Version 7.0  
REVISION DATE: 06/24/2014

Print Date 06/26/2014

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Physical State	: Solid
Form	: Non-sag gunnable paste
Color	: Dark Gray
Odor	: Naptha
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: 400 °C, 752 °F
Water solubility	: Negligible
Evaporation Rate:	: Not available.
Specific Gravity	: 1.62
% Volatile Weight	: 9 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid	: Oxidizing agents.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Titanium dioxide, CAS-No.: 13463-67-7	
Acute oral toxicity (LD-50 oral)	25,000 mg/kg ( Rat ) 5,000 mg/kg ( Rat ) 5,000 mg/kg ( Rat ) 2,000 mg/kg ( Rat ) 11,000 mg/kg ( Rat )
Acute inhalation toxicity (LC-50)	> 6.82 mg/l for 4 h ( Rat ) 3.43 mg/l for 4 h ( Rat ) 5.09 mg/l for 4 h ( Rat ) > 2.28 mg/l for 4 h ( Rat ) > 3.56 mg/l for 4 h ( Rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - WASTE DISPOSAL CONSIDERATIONS**

Disposal Method	: Dispose as hazardous waste according to all local, state, federal and provincial regulations.
-----------------	---

**ACOUSTICAL SEALANT**Version 7.0  
REVISION DATE: 06/24/2014

Print Date 06/26/2014

**SECTION 14 - TRANSPORTATION / SHIPPING DATA****TDG:**

Not Regulated

**CFR / DOT:**

Not Regulated

**IMDG:**

Not Regulated

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**Canadian Regulations:**

WHMIS Classification : D2A, D2B

This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

**Other Regulations:**

Regulatory VOC (less water and exempt solvent) : 150 g/l

**SECTION 16 - OTHER INFORMATION****HMIS Rating :**

Health	2
Flammability	1
Reactivity	0
PPE	

0 = Minimum  
 1 = Slight  
 2 = Moderate  
 3 = Serious  
 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**ACOUSTICAL SEALANT**

Version 7.0  
REVISION DATE: 06/24/2014

Print Date 06/26/2014

**Prepared by: Sewnauth Raghunandan**

**Legend**

- |   |  |
|---|--|
| ACGIH - American Conference of Governmental Hygienists        | OSHA - Occupational Safety and Health Administration     |
| DOT - Department of Transportation                            | PEL - Permissible Exposure Limit                         |
| DSL - Domestic Substance List                                 | RCRA - Resource Conservation and Recovery Act            |
| EPA - Environmental Protection Agency                         | STEL - Short Term Exposure Limit                         |
| HMIS - Hazardous Materials Information System                 | TLV - Threshold Limit Value                              |
| IARC - International Agency for Research on Cancer            | TSCA - Toxic Substances Control Act                      |
| MSHA - Mine Safety Health Administration                      | TWA - Time Weighted Average                              |
| NDSL - Non-Domestic Substance List                            | V - Volume   |
| NIOSH - National Institute for Occupational Safety and Health | VOC - Volatile Organic Compound                          |
| NTP - National Toxicology Program                             | WHMIS - Workplace Hazardous Materials Information System |