



TREMSTOP FYRE-SIL GG RUST RED-12 QT CTG

Version 5.0
 REVISION DATE: 01/29/2014

Print Date 07/16/2014

SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION

Product Information

Trade name : TREMSTOP FYRE-SIL GG RUST RED-12 QT CTG

Product code : 938874 333

Supplier : Tremco Canada division
 220 Wicksteed Avenue
 Toronto, ON M4H 1G7

Telephone : (416) 421-3300
 Emergency Phone: : (613) 996-6666

Product use : Sealant

Preparation Information

Prepared by: : Sewnauth Raghunandan
 Date: : 01/29/2014
 Telephone : (416) 421-3300

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Rust Red. Non-sag gunnable paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.
 Eyes : Direct contact may cause moderate irritation.
 Ingestion : May cause irritation to the mouth, throat and stomach.
 Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Possible skin sensitization. As a by-product of curing up to 4% Methyl Ethyl Ketoxime (MEKO) may be released within product. Repeated and prolonged exposure to MEKO can cause allergic skin reaction. It may adversely affect the blood, (methemoglobinemia and anemia). Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Organosilane may cause liver injury with fibrosis after repeated and prolonged overexposure. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Blood, Lung, Liver, Kidney

SECTION 3 : HAZARDOUS INGREDIENTS

Chemical Name	CAS-No.	Weight % Range
---------------	---------	----------------

TREMSTOP FYRE-SIL GG RUST RED-12 QT CTG

Version 5.0

Print Date 07/16/2014

REVISION DATE: 01/29/2014

Amorphous silica	7631-86-9	3.0 - 7.0
Oximino Silane	22984-54-9	3.0 - 7.0
Titanium dioxide	13463-67-7	0.1 - 1.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation	:	Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
Eye contact	:	Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
Skin contact	:	Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
Ingestion	:	Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5: FIRE / EXPLOSION HAZARDS

Flash point	:	Not available.
Method	:	Not available.
Burning rate	:	Non-flammable solid
Lower explosion limit	:	Not available.
Upper explosion limit	:	Not available.
Autoignition temperature	:	Not available.
Extinguishing media	:	If water fog is ineffective, use carbon dioxide, dry chemical or foam.
Hazardous combustion products	:	Smoke, fumes. Carbon monoxide and carbon dioxide can form. Silicon oxides and trace amounts of MEKO.
Protective equipment for firefighters	:	Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
Fire and explosion conditions	:	This product not expected to ignite under normal conditions of use.

SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Keep out of water courses. Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Do not use in confined or poorly ventilated areas. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Store in sealed containers in a cool, dry, ventilated warehouse location.

TREMSTOP FYRE-SIL GG RUST RED-12 QT CTG

 Version 5.0
 REVISION DATE: 01/29/2014

Print Date 07/16/2014

SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION
Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator, as directed by the manufacturer, when the airborne contaminant level(s) exceed the exposure limits indicated on the MSDS.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Use safety glasses if eye contact is likely.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures** : General ventilation is sufficient.

Exposure Limits

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Amorphous silica	7631-86-9	Ontario TWAEV:	3 mg/m3	Respirable particles.
		Ontario TWAEV:	10 mg/m3	Inhalable particulate.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		Ontario TWAEV:	10 mg/m3	
Titanium dioxide	13463-67-7	Ontario TWAEV:	10 mg/m3	Total dust.
		ACGIH TWA:	10 mg/m3	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	Ontario TWAEV:	0.10 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Physical State : Paste
- Form : Non-sag gunnable paste
- Color : Rust Red
- Odor : Oxime
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Negligible
- Evaporation Rate: : Not available.
- Specific Gravity : 1.37



TREMSTOP FYRE-SIL GG RUST RED-12 QT CTG

Version 5.0
REVISION DATE: 01/29/2014

Print Date 07/16/2014

% Volatile Weight : 1 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Strong acids.Strong bases.Alcohols.Water or moisture and oxidizing agents.
Stability : Material is stable under normal storage, handling, and use.
Hazardous polymerization : Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Amorphous silica, CAS-No.: 7631-86-9
Acute oral toxicity (LD-50 oral) 22,500 mg/kg (Rat) 15,000 mg/kg (Mouse)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Disposal Method : Dispose as hazardous waste according to all local, state, federal and provincial regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:
All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.



TREMSTOP FYRE-SIL GG RUST RED-12 QT CTG

Version 5.0
REVISION DATE: 01/29/2014

Print Date 07/16/2014

Canadian Regulations:

WHMIS Classification : D2A, D2B

This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Other Regulations:

Regulatory VOC (less water and exempt solvent) : 26 g/l

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	1
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Sewnauth Raghunandan

Legend

- ACGIH - American Conference of Governmental Hygienists
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration
- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System

