

Submittal Sheet

Submittal Sheet #0309049

Flat Head Coarse Thread Interior Wood to Wood Screws (280)

Product:	Item#	Description	Unit Pack
	78200YZ	8 x 2-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	3,000
	78125Z	8 x 1-1/4-in, Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	6,000
	78125YZ	8 x 1-1/4-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	6,000
	78250YZ	9 x 2- 1/2-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	2,500
	7830010YZ	10 x 3-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	1,500
	78350Z	10 x 3- 1/2-in, Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	1,000
	78350YZ	10 x 3-1/2-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	1,000
	78400Z	10 x 4-in, Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	1,000
	78400YZ	10 x 4-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	1,000
	78500YZ	10 x 5-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	1,000
	78600YZ	10 x 6-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	1,000
	78100Z	8 x 1-in, Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	8,000
	78150Z	8 x 1-1/2-in, Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	5,000
	78150YZ	8 x 1-1/2-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	5,000
	78118YZ	8 x 1-1/8-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	6,000
	78175Z	8 x 1-3/4-in, Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	4,000
	78175YZ	8 x 1-3/4-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	4,000
	78200Z	8 x 2-in, Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	3,000
	782508YZ	8 x 2-1/2-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	2,500
	783008YZ	8 x 3-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	2,500
	78250Z	9 x 2- 1/2-in, Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	2,400
	78275Z	9 x 2- 3/4-in, Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	2,000
	78275YZ	9 x 2-3/4-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	2,000
	78300Z	9 x 3", Flat Head, Coarse Thread Woody, Clear Zinc, Bulk	2,000
	78300YZ	9 x 3-in, Flat Head, Coarse Thread Woody, Yellow Zinc, Bulk	2,000

Screw Series	Designation	Head Type	Nominal Diameter	Nominal Head Diameter	Nominal Gauge- TPI	Nominal Length	Point (No#)	Thread Length	Drilling Capacity Min#	Drilling Capacity Max#	Coating
Woodys	Interior Wood	Flat Head	0.164	0.309	#8-8	1	Grabber	0.625	N/A	N/A	Z
Woodys	Interior Wood	Flat Head	0.164	0.309	#8-8	1.5	Grabber	1	N/A	N/A	Z, YZ
Woodys	Interior Wood	Flat Head	0.164	0.309	#8-8	1.25	Grabber	0.875	N/A	N/A	Z
Woodys	Interior Wood	Flat Head	0.164	0.309	#8-8	1.125	Grabber	0.75	N/A	N/A	Z
Woodys	Interior Wood	Flat Head	0.164	0.309	#8-8	1.75	Grabber	1.125	N/A	N/A	Z
Woodys	Interior Wood	Flat Head	0.164	0.309	#8-8	2	Grabber	1.375	N/A	N/A	Z, YZ
Woodys	Interior Wood	Flat Head	0.177	0.337	#9-8	2.5	Grabber	1.625	N/A	N/A	Z, YZ
Woodys	Interior Wood	Flat Head	0.177	0.337	#9-8	2.75	Grabber	1.875	N/A	N/A	YZ
Woodys	Interior Wood	Flat Head	0.177	0.337	#9-8	3	Grabber	2	N/A	N/A	Z, YZ
Woodys	Interior Wood	Flat Head	0.19	0.363	#10-8	3.5	Grabber	2.375	N/A	N/A	Z, YZ
Woodys	Interior Wood	Flat Head	0.19	0.363	#10-8	4	Grabber	2.625	N/A	N/A	Z

NOTE: Add the following to item #s when ordering YZ = Yellow Zinc Z=Clear Zinc.
FHR = Flat Head with countersinking nibs

Application: Use GRABBER Woodys with silver or yellow zinc coating for wood interior carpentry projects. Use GRABBER Woodys with GrabberGard® 1000 hr. salt spray tested screws for decks, docks, fences, patio overheads, gazebos, planter boxes, railings, etc.


Description: Extra strong 8 and 10 gauge screws in both interior and superior exterior finishes, flat ribbed head for flush seating in wood, single lead coarse thread, 8 TPI for holding power and fast penetration. #2 square for positive recess engagement and no cam out.

Directions: Use standard screw gun with depth sensitive nose piece. Suggested screw gun for optimum performance is 4 amps minimum and 0 to 4,000 rpm. Bugle Head is completely seated when the head is flush with the work surface. Overdriving may result in failure of the fastener or stripping of the head recess. For wood to wood connections, a minimum of 1 1/4" penetrations necessary using an 8 gauge screw.

Certifications: All GRABBER® screw products are manufactured in facilities that are ISO 9002 and ISO 14001 certified and approved. The fasteners comply with ASME B18.6.1, as referenced in ICC ER report ER-5280, are approved for use in structures governed by the International Building Code 2006, 2009, 2012, International Residential Building Code 2006, 2009, and 2012. ©2012 GRABBER Construction Products, Inc. GRABBER®, STREAKER®, DRIVALL®, LOX®, GRABBERGARD® and SCAVENGER® are registered trademarks of Grabber Construction Products, Inc.



Flat Head Ribbed Coarse Thread



SUBMITTAL APPROVALS:

.....
JOB NAME

CONTRACTOR

DATE

TRADEMARKS:

The following trademark used herein is owned by Grabber Construction Products, Inc.: GRABBER.

NOTICE:

We shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our Liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days of the date it was or reasonably should have been discovered.

Flat Head Coarse Thread Interior Wood to Wood Screws (280)



PRODUCT SPECIFICATIONS

Fastener Classification	Interior Wood
Fastener Head	Flat
Fastener Drive	#2 Square
Fastener Gauge	#8, #9, #10
Fastener Point	Grabber
Fastener Package Type	Packaged Screws
Fastener Package Weight	1lb Box, 5lb Box, Bulk Box
Fastener TPI	8
Fastener Coating	Yellow Zinc, Clear Zinc
Fastener Color	Gray, Yellow

STANDARD CORROSION TEST RESULTS

Finish	Test	Standard/Protocol	Results
Gray Phosphate	Salt Spray Results	ASTM B117	24 hours, no red rust
Yellow Zinc	Salt Spray Results	ASTM B117	48 hours, no red rust
Clear Zinc	Salt Spray Results	ASTM B117	24 hours, no red rust
Dracrotized	Salt Spray Results	ASTM B117	500 hours, no red rust
GrabberGard	Salt Spray Results	ASTM B117	1,000 hours, no red rust
GrabberGard	Kesternich Results	DIN 50018, 2.0L	15 cycles, no red rust
304 Stainless Steel	Salt Spray Results	ASTM B117	1000 hours, no red rust
316 Stainless Steel	Salt Spray Results	ASTM B117	1500 hours, no red rust

Grabber's approved mill keeps tight control over all production standards and processes. Grabber's mill is ISO 9001, ISO 14001 and ICC-ES certified compliant ensuring Grabber fasteners meet or exceed the highest industry standards.